

GCE

Design and Technology

Advanced GCE

Unit F524/01: Product Design: Component 1

Mark Scheme for June 2011

OCR (Oxford Cambridge and RSA) is a leading UK awarding body, providing a wide range of qualifications to meet the needs of pupils of all ages and abilities. OCR qualifications include AS/A Levels, Diplomas, GCSEs, OCR Nationals, Functional Skills, Key Skills, Entry Level qualifications, NVQs and vocational qualifications in areas such as IT, business, languages, teaching/training, administration and secretarial skills.

It is also responsible for developing new specifications to meet national requirements and the needs of students and teachers. OCR is a not-for-profit organisation; any surplus made is invested back into the establishment to help towards the development of qualifications and support which keep pace with the changing needs of today's society.

This mark scheme is published as an aid to teachers and students, to indicate the requirements of the examination. It shows the basis on which marks were awarded by Examiners. It does not indicate the details of the discussions which took place at an Examiners' meeting before marking commenced.

All Examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes should be read in conjunction with the published question papers and the Report on the Examination.

OCR will not enter into any discussion or correspondence in connection with this mark scheme.

© OCR 2011

Any enquiries about publications should be addressed to:

OCR Publications PO Box 5050 Annesley NOTTINGHAM NG15 0DL

Telephone: 0870 770 6622 Facsimile: 01223 552610

E-mail: publications@ocr.org.uk

1.	Buil	t Env	ironment and Construction			
Q	uest	ion	Expected answers	Rationale		Mark
1	(a)		 Give four design requirements for the floor structure shown in Fig.1. Justify each requirement. The floor must provide a smooth and level surface The floor must provide stability to walls The floor must resist live or imposed loads eg furniture, people etc The floor must resist dead loads eg floor finishes, partition walls, ceiling finishes etc The floor must provide an acceptable level of fire resistance The floor must provide an acceptable level of sound insulation The floor must provide an acceptable level of heat loss The floor must provide resistance to dampness and 	Clear statement and justification required for 1 mark. Must be related to the floor – no marks for generic responses. Four justified design requirements. Give one mark if two valid points given but not fully justified.	4x1	4
	(b)		 condensation. Describe two examples where ergonomics has influenced the design of flooring. Use sketches and/or notes where appropriate. The amount of deflection/spring of the floor to ease stress on leg/ankle joints and muscle fatigue ie when used for dance floors, aerobic/fitness centres, recreation rooms, workshops Affects on hearing where a lightweight floor structure transmits impact noise to another room. A dense ie, concrete floor would absorb the noise Texture of the floor finish for non-slip applications ie wet-rooms, changing rooms, Colour/luminance to contrast the floor surface with the walls to aid visually impaired people 	brief description 1 mark detailed description with clear indication and description of the factor 2 marks Two factors clearly described. Allow reference to given product.	2x2	4

1. Built En	vironment and Construction			
Question	Expected answers	Rationale		Mark
	No changes in the level of the floor or obstructions ie thresholds at openings to comply with the DDA.			
(c)	Describe two ways in which designs relating to the Built Environment and Construction can be legally protected. • Design rights-protection in UK of design • Registered designs – ownership of appearance/shape/pattern • Patents – protection against copying of technical/functional aspects • Copyright – protects original ideas – books/software/works of art/music.	Brief explanation 1 mark Detailed explanation 2 marks Two examples clearly explained. Allow reference to given product.	2x2	4
(d)	Explain two ways in which consumers can be assured that they are purchasing a quality product in relation to the Built Environment and Construction. Brand reliability/reputation Treports equality control systems in manufacturing process Consumer reports equality warranty British Board of Agreement Certificate Offer of a manufacturer's warranty Customer reviews Try-before-you-buy Paying a premium price for the product The use of quality materials in the product.	Allow credit for each if candidate refers to BSI and CE standards in each part. Full credit if candidate has identified the difference between these (UK and Europe). brief explanation with example 1 mark detailed explanation with example 2 mark Two features clearly explained.	2x2	4

1. Built Env	vironment and Construction			
Question	Expected answers	Rationale		Mark
(e) (i)	State a suitable specific material for the finish to the floor structure shown in Fig.1. Give two properties or characteristics that make the material suitable for this use.			
	 Material Tongue and groove softwood boarding Hardwood strip boarding Particle board (flooring grade) including laminated Plywood (flooring grade) Wood blocks Carpet and carpet tiles Vinyl sheet and tiles. 	Award 1 mark for other appropriate material not listed. 1x1 mark	1	
	Properties or characteristics Resistant to wear Resistant to water Resistant to indentation and impact Resistant to chemicals Appearance Ease of cleaning Fire resistance Slipperiness Cost Warmth Resistant to impact sound.	Award 1 mark for other appropriate property/characteristic. 2x1 mark	2x1	3

1. Built En	vironment and Construction			
Question	Expected answers	Rationale		Mark
(ii)	Describe, in detail, how an upper floor structure can provide lateral restraint to an external cavity wall. Use annotated diagrams to support your answer. Joists parallel to the wall			
	 Description and sketch to include the use of: Galvanised steel restraint straps fastened to the top edge of a minimum of three joists and hooked over the internal leaf of the cavity wall. The straps used at no more than 2m centres A packing piece used between the face of the inner leaf and the adjacent joist Noggings fastened between each joist to support the steel strap. The noggings should be at least half of the joist depth. Joists at right angles to the wall Description and sketch to include the use of: Galvanised restraint hangers supporting the ends of the joists and hooked over the inner leaf of the cavity wall. 	Level 1 (0-2 marks) Some features outlined (up to 2), very limited description. Level 2 (3-4 marks) Key features identified and reasonably well described. Level 3 (5-6 marks) Process fully described, key features and technical details identified, Answer must include details of both situations for full marks. Award maximum of Level 1 if an inappropriate process for the product (or the batch number) is described. Quality of description and communication Basic sketches with limited annotation 1 mark Good sketches with main features identified and labelled 2 marks Detailed sketches with clear annotation 3 marks Maximum of 1 mark if no sketch used Award full 3 marks if candidate demonstrates good communication. Award credit where possible if response doesn't link to chosen material.	6	9

1. Built Env	vironment and Construction		
Question	Expected answers	Rationale	Mark
(f)	 Discuss the factors that influence scale of production in the domestic housing market. Government policy/initiatives regarding requirements for affordable homes, key workers, mixed-use/tenure for families, single people, sheltered accommodation, owner-occupier, social housing, privately rented etc Government grants for the regeneration of brownfield sites Local Authority release of land in green belts/wedges for housing The supply of land with planning permission Government fiscal/monetary policy influencing the cost and availability of finance. The raising of interest rates reducing demand or inflation causing a rise in house prices Planning policy in terms of density of houses allowed per hectare Planning policy in terms of rural communities aesthetics/style of existing houses and the need to use local materials and vernacular designs More demanding Building Regulations in terms of houses being zero carbon rated Modern methods of production ie factory prefabrication allowing the standardisation of components and modular/volumetric pods Cost of land/materials/labour together with a shortage of skilled labour. 	Level 1 (0-2 marks) Some measures outlined, bullet points (usually focused on one issue) no further or very limited discussion, limited use of examples. Level 2 (3-5 marks) One or two measures described with some discussion. Appropriate use of technical vocabulary demonstrating a good understanding of the issues. Introduction of one example. Level 3 (6-8 marks) Clear, cogent and well – structured answer with two or three measures well explained. Good use of examples and additional evidence to support discussion. Good use of technical vocabulary. Award level 3 for a very detailed, clear response with no examples.	8
		Question 1	1 Total 36

2.	Engir	ering			
C	Questic	Expected answers	Additional Guidance		Mark
2	(a)	Give four design requirements for the decorative screen shown in Fig. 2. Justify each requirement. Should be aesthetically pleasing so as not to detract from building design Able to be firmly fixed in place for safety Able to be removed if needed for maintenance No sharp corners or edges that could cause injury High enough to prevent someone falling over No gaps large enough for a child to get through or caught in Sufficiently open to allow minimal restriction to view from balcony Resistant to weather for outside use.	Clear statement and justification required for a mark.	4x1	4
	(b)	Describe two examples where ergonomics has influenced the design of the decorative metal screen on a hotel balcony shown in Fig. 2. Use sketches and/or notes where appropriate. Overall height of screen Height of screen base above floor Maximum size of 'gaps' in screen Thickness of metal used in construction of screen Position/security of fixings.	brief description 1 mark detailed description with clear indication and description of example 2 marks anthropometric examples must be specific and relevant Two examples clearly described. Allow reference to given product.	2x2	4
	(c)	Describe two ways in which the design of engineered products can be legally protected. Design rights Copyrights Registered design Patenting Trademarks.	brief description 1 mark detailed description 2 marks Two ways clearly described Allow reference to given product.	2x2	4

Enginee			1	T
Question	Expected answers	Additional Guidance		Marl
(d)	Explain two ways in which consumers can be assured that they are purchasing a quality engineered product. BSI/ISO approval Trades description act Sale of goods act Personal recommendation Brand loyalty	Allow credit for each if candidate refers to BSI and CE standards in each part. Full credit if candidate has identified the difference between these (UK and Europe). brief description 1 mark detailed description 2 marks Two ways clearly described.	2x2	4
(e) (i)	 Offer of a manufacturer's warranty Customer reviews Try-before-you-buy Paying a premium price for the product The use of quality materials in the product. State a suitable specific metal for the scroll shown in Fig.3.			
	Give two properties or characteristics that make the metal suitable for this use. Material Steel – low carbon/mild Stainless steel aluminium alloy. Properties or characteristics will include ease of working/shaping relative cost relative strength (small section material) Ease of surface finishing (for corrosion resistance) Corrosion resistance Weldability.	1 mark Properties must relate to material stated and be relevant eg not relative cost or ease of finishing if stainless steel stated. 2x1 mark	1 2x1	3

	Additional Guidance	Ma
Describe, in detail, how the scroll shown in Fig. 3 would be manufactured. Give details of any special tooling and quality control checks that would be used. Use a flowchart and /or annotated diagrams to support your answer.	Level 1 (0-2 marks) Some stages outlined (up to 2);very limited description; limited. Level 2 (3-4 marks) Key stages presented; reasonably well described with	
 Cut metal strip to length (QC – gauge to ensure consistency) Mark position of holes (QC – template to ensure equi-distant from ends) Drill holes (QC – jig to position accurately or punch and use M/C vice) Bend scroll on each end of strip (heat required if done manually) using former/scroll iron (QC – use template to check accuracy of shape and size). Note:- holes may be drilled after scrolling but must show use of jig or other means of ensuring accuracy when 	key features identified. Level 3 (5-6 marks) Process fully described; key features and technical details identified. Answer must include detail of quality control checks for full marks. Award maximum of Level 1 if an inappropriate process for the product (or the batch number) is described. Quality of description and communication Basic diagrams/chart with limited annotation 1 mark Good diagrams/chart with main features identified and labelled 2	6
 Remove all sharp and rough edges from finished scroll (QC – visual check). Note:- If special purpose/hydraulic forming machine is used, annotated diagrams needed to explain operation. Award credit for candidates who describe the adding of a suitable surface finish, eg paint, powder coat etc 	Detailed diagrams/chart with clear annotation 3 marks Max 1 mark in this strand if no diagrams or flowchart used Award full 3 marks if candidate demonstrates good communication. NB A sequence of manufacturing stages can be given in place of a flowchart.	3 9
	 Checks that would be used. Use a flowchart and /or annotated diagrams to support your answer. Cut metal strip to length (QC – gauge to ensure consistency) Mark position of holes (QC – template to ensure equi-distant from ends) Drill holes (QC – jig to position accurately or punch and use M/C vice) Bend scroll on each end of strip (heat required if done manually) using former/scroll iron (QC – use template to check accuracy of shape and size). Note:- holes may be drilled after scrolling but must show use of jig or other means of ensuring accuracy when drilling Remove all sharp and rough edges from finished scroll (QC – visual check). Note:- If special purpose/hydraulic forming machine is used, annotated diagrams needed to explain operation. Award credit for candidates who describe the adding of a 	Give details of any special tooling and quality control checks that would be used. Use a flowchart and /or annotated diagrams to support your answer. Cut metal strip to length (QC – gauge to ensure consistency) Mark position of holes (QC – template to ensure equi-distant from ends) Drill holes (QC – jig to position accurately or punch and use M/C vice) Bend scroll on each end of strip (heat required if done manually) using former/scroll iron (QC – use template to check accuracy of shape and size). Note:- holes may be drilled after scrolling but must show use of jig or other means of ensuring accuracy when drilling Remove all sharp and rough edges from finished scroll (QC – visual check). Note:- If special purpose/hydraulic forming machine is used, annotated diagrams needed to explain operation. Award credit for candidates who describe the adding of a

Question	Expected answers	Additional Guidance	Mark
(f)	Discuss the factors that influence scale of production of engineered products. Possible issues: demand economic factors/wages/energy material availability	Level 1 (0-2 marks) Some issues outlined, bullet points (usually focused on one issue) no further or very limited explanation, limited use of examples or supporting evidence.	
	 manufacturing capacity commercial back-up nature of product /number of component parts/assembly/complexity of product. 	Level 2 (3-5 marks) One or two issues described with some explanation. Appropriate use of technical vocabulary demonstrating a good understanding of concept. Introduction of one example or supporting evidence.	
	 Examples/evidence specific product – one-off/batch/high volume specific detail – economic factors/manufacturing specific commercial requirement – example details of resources (physical and human). 	Level 3 (6-8 marks) Clear, cogent and well structured response with two or three issues well explained. Good use of examples and additional evidence to support discussion. Good use of technical vocabulary. Award level 3 for a very detailed, clear response with no examples.	8

3.	Food				
Q	uestion	Expected answers	Rationale		Mark
3	(a)	 Give four design requirements for a lemon meringue pie shown in Fig. 4. Justify each requirement. Function: dessert product in a pastry case Tangy lemon flavour sauce base, set to a depth of 2.5 cm Natural lemon colour base to make it look appealing Meringue topping to a depth of 6 cm in the middle to give a substantial portion size Six portion size for a family product Crisp meringue so that the raw egg is well cooked Pastry Base of shortcrust pastry so that it will easily cut into portions Lemon base must be set to cut into neat slices. 	Clear statement and justification required for a mark. Must be related to product – no marks for generic or obvious responses. Do accept lemon flavour/meringue topping must be more specific. Four justified design requirements. Give one mark if two valid points given but not fully justified.	4x1	4
	(b)	Describe two examples where ergonomics has influenced the design of the pie slice as shown in Fig.2. Use sketches and/or notes where appropriate. Handle/grip/diameter/length Size of the 'lifting' part of the pie slice/width is portion sized, length will support an average sized pie or cake Gap between the handle and the pie support part allows user to give additional support from their thumb.	brief description 1 mark detailed description with clear understanding of example 2 marks Two different examples clearly described. Allow reference to given product.	2x2	4

3. Food				
Question	Expected answers	Rationale		Mark
(c)	 Describe two ways in which the design of food products can be legally protected. Patent gives the designer protection copying of the technical and functional aspects Design rights concerns the rights of the creator unless a third party commissions the work Registered designs give you ownership rights for the appearance of the product, Trademark identifies and distinguishes its products (word/name logo/slogan). 	brief description 1 mark detailed description 2 mark Two ways clearly described Eg Recipes Product names Product ranges eg 'Finest' 'Value' Packaging designs Allow reference to given product.	2x2	4
(d)	 Explain two ways in which consumers can be assured that they are purchasing a quality food product. Quality assurance by: Use of logos that guarantee high standards eg organic Quality control checks carried out HACCP systems in place in manufacturing Reputation of a reliable food manufacturing company Descriptors eg luxury product Date marking – Use by and best before date Ingredient list eg British Beef/Free range Luxury range products with specific named ingredients Offer of a manufacturer's warranty 	Allow credit for each if candidate refers to BSI and CE standards in each part. Full credit if candidate has identified the difference between these (UK and Europe). Statement 1 mark Statement explained 1 mark Two quality assurance systems clearly explained. Do not accept 'sell by date'.	2x2	4
	 Customer reviews Try-before-you-buy Paying a premium price for the product The use of quality materials in the product. 			

3. Food				
Question	Expected answers	Rationale		Mark
(e) (i)	State a suitable specific ingredient for making meringue. Give two properties or characteristics that make the ingredient suitable for this use.			
	Ingredient	1x1 mark	1	
	Egg white (albumin)Castor sugar.	Must state either egg white (albumen) Or castor sugar	2x1	
	Properties Egg white Egg white can be aerated due the ability of the ovalbumin (egg protein) to stretch and hold air When egg white is whisked the proteins are denatured and they uncoil This forms a 3D air/liquid structure that can hold air. The foam is stable but can be affected by other ingredients.	Do not accept the words egg or sugar on their own. 2x1 mark for any of two of the points listed. Award 1 mark for other appropriate point.		
	 Castor Sugar Interferes with the bonds that form when egg whites uncoil as they are whisked Whisking time is increased therefore the foam is denser The foam is much more stable. 			3

Question Expected answers	Rationale		Mari
Coagulation Expected answers	Level 1 (0-2 marks) Some stages outlined (up to 2), very limited description. Level 2 (3-4 marks) Key stages presented, reasonably well described with key features identified. Level 3 (5-6 marks) Process fully described, key features and technical details identified, Answer must include detail of scientific principles for full marks. To achieve full marks, the described process must be relevant for the batch size. Award maximum of Level 1 if an inappropriate process for the product (or the batch number) is described. Quality of description and communication Basic information with limited scientific knowledge 1 mark Good detail with main scientific principles identified and labelled 2 marks Detailed scientific principles 3 marks Award full 3 marks if candidate demonstrates good communication. NB A sequence of manufacturing stages can be given in place of a flowchart.	6	Mari

Question	n Expected answers	Rationale	Mark
(f)	Discuss the factors that influence scale of production in the Food Industry. Issues Demand/quantity of products to be produced economic factors/wages/energy material availability/seasonal products manufacturing capacity of equipment commercial backup nature of product /skill level required results of small scale factory trial scaling up of the recipe. Examples/evidence specific product – one off – wedding cake batch – cook chill high volume – baked beans specific detail re – economic factors/manufacturing specific commercial requirement.	Level 1 (0-2 marks) Some issues outlined, bullet points (usually focused on one issue) no further or very limited explanation, limited use of examples or supporting evidence. Level 2 (3-5 marks) One or two issues described with some explanation. Appropriate use of technical vocabulary demonstrating a good understanding of the concept. Introduction of one example or supporting evidence. Level 3 (6-8 marks) Clear, cogent and well – structured response with two or three issues well explained. Good use of examples and additional evidence to support discussion. Good use of technical vocabulary Award level 3 for a very detailed, clear response with no examples.	8
		Question 3	Total

4.	Grap	hic I	Products			
C	Question		Expected answers	Rationale		Mark
4	(a)		 Give four design requirements for the printed credit card shown in Fig. 5. Justify each requirement. It must be easy to read, graphic material should not obscure digits It should reflect the corporate identity of the company The signature strip should be large enough to sign It must be flexible so it maintains its shape when stored It should contain a holographic image for security purposes Contact telephone numbers should be printed onto the card for security purposes It should be durable and not snap It should be easy to store in a wallet eg round edges. 	Clear statement and justification required for a mark. Must be related to product – no marks for generic responses. Aesthetic/environment response must have example for mark. Four justified design requirements. Give one mark if two valid points given but not fully justified.	4x1	4
	(b)		Describe two examples where ergonomics has influenced the design of the credit card shown in Fig.5. Use sketches and/or notes where appropriate. Size of the card – easy to fit into a wallet Universal size The shape of the card – rounded corners, sometimes has a wave cut out of one end Durable, easy to use Clear graphical design – easy to read the information printed on the card.	brief description 1 mark detailed description with clear indication and description of example 2 marks must be methods of producing prototypes – Using different materials. Two examples clearly described. Allow reference to given product.	2x2	4

. Graphic	Products			
Question	Expected answers	Expected answers Rationale		Mark
(c)	 Describe two ways in which the design of graphic products can be legally protected. Design rights-protection in UK of design Registered designs – ownership of appearance/shape /pattern Patents – protection against copying of technical/functional aspects Copyright– protects original ideas–books/software/works of art/music. 	brief description 1 mark detailed description 2 mark Allow reference to given product.	2x2	4
(d)	Explain two ways in which consumers can be assured that they are purchasing quality graphic products. Brand reliability/reputation Try-before-you-buy Paying a premium price for the product.	Allow credit for each if candidate refers to BSI and CE standards in each part. Full credit if candidate has identified the difference between these (UK and Europe). brief explanation with example 1 mark detailed explanation with example 2 mark Two examples clearly explained.	2x2	4
(e) (i)	State a suitable specific material for the credit card. Give two properties or characteristics that make the material suitable for this use. PVCA – polyvinyl chloride acetate Allow ABS, polypropylene, PVC, uPVC NOT acrylic Easily manufactured using high speed production Aesthetically appropriate Easy to die cut.	award 1 mark for other appropriate material not listed 1x1 mark Award 1 mark for other appropriate property/characteristic.	1x1 2x2 2x1	
		2x1 mark		3

4. Graphic Products			
Question	Expected answers	Rationale	
(ii)	Describe, in detail, how the background image would be applied to the credit card blank, manufactured in a batch of 100 000. Use a flowchart and/or annotated diagrams to support your answer.	Sketches can be used to support the explanation	
	Part A Silk Screen Printing. Standard explanation of the process, it should include sketches:	Level 1 (0-2 marks) Some stages outlined (up to 2), very limited description.	
	 Origination of artwork using a suitable/relevant software package A stencil is manufactured using a photochemical process Two types of threads for screen fabric, monofilament is used primarily for commercial printing as it is easier to clean. Normally made from polyester – strong and stable An emulsion is applied to the screen, this is a light sensitive material which hardens when exposed to light Normally the emulsion is presensitized allowing it to be used immediately The screen is exposed to a positive film image in a vacuum frame, it is then normally washed, the unexposed areas of the emulsion simply wash away leaving the stencil in place The stencil/emulsion defines the area of the image which will be printed Separate stencils are used for each colour eg cmyk Colour applied and then squeegeed through 	Level 2 (3-4 marks) Key stages presented, reasonably well described with key features identified. Level 3 (5-6 marks) Process fully described, key features and technical details identified, Answer must include correct terminology and an understanding of the difference between this type of printing and litho. To achieve full marks, the described process must be relevant for the batch size. Award maximum of Level 1 if an inappropriate process for the product (or the batch number) is described. Quality of description and communication Basic sketch/chart with limited annotation 1 mark Good sketch/chart with main features identified and labelled 2 marks Detailed sketch/chart with clear annotation 3 marks Max 1 if no sketch used Award full 3 marks if candidate demonstrates good	6

1. Graphic Products			
Question	Expected answers	Rationale	Ma
•	Colour must be dry before moving on to the next process, can be dried using UV, UV inks may also be used Screen should be placed accurately above the image, if classroom based this should be mentioned Process is repeated.	NB A sequence of manufacturing stages can be given in place of a flowchart. Award credit where possible if response doesn't link to chosen material.	3
in lss	iscuss the factors that influence scale of production the Graphics Industry. sues demand economic factors/wages/energy material availability manufacturing capacity commercial backup nature of product /number of component parts/assembly/complexity of product. xamples/evidence specific product – one/off/batch /high volume specific detail re – economic factors/manufacturing specific commercial requirement.	Level 1 (0-2 marks) Some issues outlined, bullet points (usually focused on one issue) no further or very limited explanation, limited use of examples or supporting evidence. Level 2 (3-5 marks) One or two issues described with some explanation. Appropriate use of technical vocabulary demonstrating a good understanding of concept. Introduction of one example or supporting evidence. Level 3 (6-8 marks) Clear, cogent and well – structured response with two or three issues well explained. Good use of examples and additional evidence to support discussion. Good use of technical vocabulary Award level 3 for a very detailed, clear response with no examples.	8

5.	Manu	facturing			
C	luesti	on Expected answers	Additional Guidance		Mark
5	(a)	Give four design requirements for the chair shown in Fig. 6. Justify each requirement. Stable to prevent toppling Strong enough to take large adults weight Comfortable for person to sit on Give adequate support for person Safe construction with no 'pinch points' Well upholstered for comfort and durability Aesthetically pleasing to fit into surroundings Finish applied to wooden frames for smoothness and protection Ergonomics/anthropometric reference.	Clear statement and justification required for a mark. Must be related to product – no marks for generic responses. Four justified design requirements. Give one mark if two valid points given but not fully justified.	4x1	4
	(b)	Describe two examples where ergonomics has influenced the design of the chair shown in Fig. 6. Use sketches and/or notes where appropriate. Angle/height of chair back Height of chair seat Depth of seat (front to back) Width of chair between frames Width of frame 'armrest' Height of armrest Hardness of padding Choice of upholstery material.	brief description 1 mark detailed description with clear indication and description of example 2 marks anthropometric examples must be specific and justified Two examples clearly described. Allow reference to given product.	2x2	4

5. Manu	acturing			
Questi	n Expected answers	Additional Guidance		Mark
(c)	Describe two ways in which the design of manufactured products can be legally protected. Design rights Copyrights Registered design Patenting Trademarks.	brief description 1 mark detailed description 2 marks Two ways clearly described. Allow reference to given product.	2x2	4
(d)	Explain two ways in which consumers can be assured that they are purchasing a quality manufactured product. BSI/ISO approval Trades description act Sale of goods act Personal recommendation Brand loyalty Offer of a manufacturer's warranty Customer reviews Try-before-you-buy Paying a premium price for the product The use of quality materials in the product.	Allow credit for each if candidate refers to BSI and CE standards in each part. Full credit if candidate has identified the difference between these (UK and Europe). brief explanation 1 mark detailed explanation 2 marks Two ways clearly described.	2x2	4
(e)	(i) State a suitable specific material for the side frame shown in Fig. 7. Give two properties or characteristics that make the material suitable for this use. Material Suitable hardwood, eg beech, birch, maple, mahogany, cherry NOT MDF	Accept 'plywood' with no specified timber. 1 mark	1	

5. Manufac		A 1 120 1 A 1 1		
Question	Expected answers	Additional Guidance		Mark
	 Laminated strips/veneers of hardwood. Properties or characteristics will include Strength/closeness of grain Visual appearance Sustainable resource Relative cost Suitability for bending/laminating. 	Award 1 mark for other appropriate property/characteristic. 2x1 mark	2x1	3
(ii)	Describe, in detail, how the side frame shown in Fig. 7 would be manufactured as a batch of 5 000. Include details of any special equipment and quality control checks that would be used. Use a flowchart and/or annotated diagrams to support your answer. Cut timber/strips to length Steam solid timber/glue strips for laminating (QC – control steaming time/ensure even coverage of strips with adhesive) Clamp softened timber/assembled strips onto preprepared former (QC – ensure full contact with former – visual; remove excess adhesive from edges of laminations) Drying timber/curing adhesive Remove completed arm from former (QC – ensure fully dried/cured) Trim ends of arm and finish to shape/size (QC – check against template for accuracy) Drill holes (QC – use of jig to ensure alignment) Final sanding Apply finish Final QC check	Level 1 (0-2 marks) Some stages outlined (up to 2),very limited description, limited. Level 2 (3-4 marks) Key stages presented, reasonably well described with key features identified. Level 3 (5-6 marks) Process fully described, key features and technical details identified, Answer must include detail of quality control checks for full marks. To achieve full marks, the described process must be relevant for the batch size. Award maximum of Level 1 if an inappropriate process for the product (or the batch number) is described. Quality of description and communication	6	

Question	Expected answers	Additional Guidance	Mar
	Fully/semi-automated process to include the above stages; details required of special equipment/procedures at each stage.	Basic diagrams/chart with limited annotation 1 mark Good diagrams/chart with main features identified and labelled 2 marks Detailed diagrams/chart with clear annotation 3 marks Max 1 mark in this strand if no diagrams or flowchart used. Award full 3 marks if candidate demonstrates good communication. NB A sequence of manufacturing stages can be given in place of a flowchart. Award credit where possible if response doesn't link to chosen material.	3
(f)	Discuss the factors that influence scale of production in the Manufacturing Industry. Issues demand conomic factors/wages/energy material availability manufacturing capacity commercial back-up nature of product /number of component parts/assembly/complexity of product. Examples/evidence specific product — one-off/batch/high volume	Level 1 (0-2 marks) Some issues outlined, bullet points (usually focused on one issue) no further or very limited explanation, limited use of examples or supporting evidence. Level 2 (3-5 marks) One or two issues described with some explanation. Appropriate use of technical vocabulary demonstrating a good understanding of concept. Introduction of one example or supporting evidence. Level 3 (6-8 marks) Clear, cogent and well structured response with two or	
	 specific detail – economic factors/manufacturing specific commercial requirement – example details of resources (physical and human). 	three issues well explained. Good use of examples and additional evidence to support discussion. Good use of technical vocabulary. Award level 3 for a very detailed, clear response with no examples.	8

6.	Resi	stant materials	S			
C	luesti	on	Expected answers	Rationale		Mark
6	(a)	material Justify e The spi The cau The wh The be The pre The ma	r design requirements for the holder of art s shown in Fig 8. each requirement. e holder must be washable as art materials may	Clear statement and justification required for a mark Must be related to product – no marks for generic responses Four justified design requirements. Give one mark if two valid points given but not fully justified.	4x1	4
	(b)	• Ha • Ha • We • Na	e two examples where ergonomics has ed the design of the holder of art materials in Fig. 8. It these and/or notes where appropriate. Indle thickness, indle width lance of holder for ease of carrying eight of unit indicates in the prevent banging against legen carrying.	brief description 1 mark detailed description with clear indication and description of example 2 marks anthropometric examples must have reference to body eg hand grip for handle Two examples clearly described. Allow reference to given product.	2x2	4

6. Resistan	t materials			
Question	Expected answers	Rationale		Mark
(c)	 Describe two ways in which the design of resistant material products can be legally protected. Design rights-protection in UK of design Registered designs – ownership of appearance/shape /pattern Patents – protection against copying of technical/functional aspects Copyright – protects original ideas–books/software/works of art/music. 	brief description 1 mark detailed description 2 mark Two ways clearly described Allow reference to given product.	2x2	4
(d)	Explain two ways in which consumers can be assured that they are purchasing a quality resistant materials product. Brand reliability/reputation Try-before-you-buy Paying a premium price for the product.	Allow credit for each if candidate refers to BSI and CE standards in each part. Full credit if candidate has identified the difference between these (UK and Europe). Stage 1 mark Impact explained 1 mark Two stages clearly explained.	2x2	4

6. Resistan	t materials			
Question	Expected answers	Rationale		Mark
(e) (i)	State a suitable specific material for the holder of art materials shown in Fig. 8. Give two properties or characteristics that make the material suitable for this use.			
	Material			
	 abs; polypropylene; aluminium; mdf plywood pine, deal, beech, cherry. Properties or characteristics easily formed to required shape; produces rigid structure; takes a quality finish; durable, takes knocks. 	award 1 mark for other appropriate material not listed 1x1 mark Award 1 mark for other appropriate property/characteristic. 2x1 mark	1 2x1	3

6. Resistant	materials	6. Resistant materials					
Question	Expected answers	Rationale	Mark				
(ii)	Describe, in detail, how the holder of art materials shown in Fig.8 would be manufactured as a batch of 100. Include details of any jigs and formers used. Use a flowchart and/or annotated diagrams to support your answer.	Level 1 (0-2 marks) Some stages outlined (up to 2), very limited description.					
	Could be a combination of materials (base/handle) and manufacturing processes. Plastic forming mark out/cut developments (batch of 100)	Level 2 (3-4 marks) Key stages presented, reasonably well described with key features identified. Level 3 (5-6 marks)					
	 use strip heater/bending jig to form base/sides secure corners (adhesive, corner strip turn, shape and locate handle. 	Process fully described, key features and technical details identified, Answer must include detail of specialist tooling for full marks. To achieve full marks, the described process must be	6				
	 Plastic assembly mark out parts (batch of 100) cut and prepare shapes assemble using appropriate cement/adhesive and jig/former to hold whilst setting handle made and secured edges finished. 	Award maximum of Level 1 if an inappropriate process for the product (or the batch number) is described. Quality of description and communication					
	Laser cutting/thermoforming design created CAD print details setup/speed, thickness of material laser cutter set up, auto focus laser cut auto removal/replacement thermoformed using line bend system held until shape set	Basic sketch/chart with limited annotation 1 mark Good sketch/chart with main features identified and labelled 2 marks Detailed sketch/chart with clear annotation 3 marks Max 1 if no sketch used Award full 3 marks if candidate demonstrates good communication. NB A sequence of manufacturing stages can be given in place of a flowchart.	3				

F524/01 Mark Scheme June 2011

6. Resistant materials			
Question	Expected answers	Rationale	Mark
Other parts comparts comparts comparts comparts comparts comparts and the comparts are comparted to the comparts are comparts as the comparts are comparts as the comparts are compared to the comparts are compared to the compare	arts assembled (adhesive/cement) or all buld be designed to join/clip together nay be flame polished handle.	Award credit where possible if response doesn't link to chosen material.	9

6. Resistant	t materials		
Question	Expected answers	Rationale	Mark
(f)	Discuss the factors that influence scale of production of resistant material products. Issues demand economic factors/wages/energy material availability manufacturing capacity commercial backup nature of product /number of component parts/assembly/complexity of product. Examples/evidence specific product – one/off/batch /high volume specific detail re – economic factors/manufacturing specific commercial requirement.	Level 1 (0-2 marks) Some issues outlined, bullet points (usually focused on one issue) no further or very limited explanation, limited use of examples or supporting evidence. Level 2 (3-5 marks) One or two issues described with some explanation. Appropriate use of technical vocabulary demonstrating a good understanding of concept. Introduction of one example or supporting evidence. Level 3 (6-8 marks) Clear, cogent and well – structured response with two or three issues well explained. Good use of examples and additional evidence to support discussion. Good use of technical vocabulary. Award level 3 for a very detailed, clear response with no examples.	8
		Question 6	Total 36

7. Sys	tems	and Control			
Ques	tion	Expected answers	Rationale		Mark
7 (a)		 Give four design requirements for a cordless food mixer shown in Fig. 9. Justify each requirement. The mixer must be powerful enough to mix all common food mixtures, including stiffer ones The mixer must not be too heavy and must be balanced so that it is comfortable and not tiring to hold The beaters must be removable for easy washing (eg in a dishwasher) The mixer's casing must be able to be cleaned as it will get splashed by food products during use There must be simple and clear controls for on/off/speed etc so that the product is user friendly The cordless battery must last at least long enough to carry out a food preparation task to make the mixer fit for purpose There must be a minimal risk of injury if fingers accidentally become trapped in the beaters so that it is not dangerous to children The speed must be variable to provide the user with full control over the mixing task. 	Clear statement and justification required for a mark. Must be related to product – no marks for generic responses. Four justified design requirements. Give one mark if two valid points given but not fully justified.	4x1	4
(b)		Describe two examples where ergonomics has influenced the design of the cordless food mixer shown in Fig. 9. Use sketches and/or notes where appropriate. Handle thickness, width and length – so that the mixer can be held securely and comfortably Finger aperture dimensions – so that all users can hold the mixer	brief description 1 mark detailed description with clear indication and description of example 2 marks anthropometric examples must have reference to body eg length of thumb so that control position can be determined. Two examples clearly described. Allow reference to given product.	2x2	4

7. Systems	and Control			
Question	Expected answers	Rationale		Mark
	 Balance of mixer for ease of holding during use – the designer can position the balance point to minimise strain on the user's wrist Weight of mixer – too heavy and it is tiring to hold, too light and the product will jump and jitter in the user's hand during use Positioning of controls for easy operation by thumb – so that the mixer can be easily and safely operated with one hand whilst the other hand holds the mixing bowl. 			
(c)	 Describe two ways in which the design of electronic products can be legally protected. Patent protection of design function – to protect new, inventive and useful claims Intellectual property protection and copyright – the rights granted to an author or creator of an original work, including drawings and software Registered design protection – could refer to product logos, distinctive product shapes, product music or sound effects Registered trademark protection – to protect a product logo or name or a unique icon related to a product during its use. 	brief description 1 mark detailed description 2 mark Two ways clearly described. Allow reference to given product.	2x2	4

7. Systems	and Control			
Question	Expected answers	Rationale		Mark
(d)	 Explain two ways in which consumers can be assured that they are purchasing a quality electronic product. Brand reliability/reputation 3rd party testing – products built to BSI Quality control systems in the manufacturing process Consumer reports eg Which Consumer star-rating of products through webbased retailers Offer of a manufacturer's warranty Customer reviews Try-before-you-buy Paying a premium price for the product The use of quality materials in the product. 	Allow credit for each if candidate refers to BSI and CE standards in each part. Full credit if candidate has identified the difference between these (UK and Europe) Stage 1 mark Impact explained 1 mark Two stages clearly explained	2x2	4
(e) (i)	Sketch a labelled diagram to show a mechanical system which could be used in a cordless food mixer to transfer rotary motion from the electric motor through 90 degrees and provide a speed reduction to drive the beaters. Worm drive system or bevel gear system Diagram to show: Labelled component parts Method of transferring motion through 90 degrees Method of providing speed reduction. It is not necessary to show how the two beaters are driven, nor how they rotate in contrary directions.	Labelled components in the gear system 1 mark Clear diagrammatic representation of motion transferred through 90 degrees 1 mark (A worm or bevel gear system is expected, but credit candidates who correctly draw other systems.) Clear indication of how speed reduction is achieved 1 mark (Award mark if this is apparent from the relative sizes of the gear components used.)	3x1	3

7. Systems and Control						
Quest	ion	Expected answers	Rationale		Mark	
	(ii)	Describe in detail how pulse width modulation can be used to control the speed of a DC electric motor. Use annotated diagrams to support your answer. Your answer should include a circuit diagram. Sketches and notes to convey the following information:	Level 1 (0-2 marks) PWM process outlined (up to 2), very limited description.			
		 Principle of PWM – rapid on/off pulsing of motor at full power Understanding that this pulsing takes place very rapidly (typically about 1kHz frequency) Waveforms to show mark:space ratio of PWM Method of speed control – varying mark:space ratio (also known as the duty cycle) Use of astable circuit to provide pulses Astable circuit diagram (eg 555, NAND-gate astable, Schmitt NAND relaxation oscillator, transistor multivibrator or any other astable circuit) Method of varying the mark:space ratio (NOT just the frequency). This will depend on the actual astable circuit drawn. 	Level 2 (3-4 marks) Key diagrammatic information presented, reasonable understanding, attempt at circuit or system diagram. Level 3 (5-6 marks) Process fully described, key features and technical details identified. Answer must include circuit diagram for full marks. To achieve full marks, the described process must be relevant for the batch size. Award maximum of Level 1 if an inappropriate process for the product (or the batch number) is described. Quality of description and communication Basic sketches with limited annotation 1 mark Good sketches with main features	6	9	
			Identified – correct circuit schematics used 2 marks Detailed sketches with clear annotation and competent circuit schematic layout 3 marks Max 1 if no sketches used Award full 3 marks if candidate demonstrates good communication. NB A sequence of manufacturing stages can be given in place of a flowchart.			

7. Systems	and Control		
Question	Expected answers	Rationale	Mark
(f)	Discuss the factors that influence scale of production of electronic products. Issues Demand – based on current demand for similar products and future predictions based on consumer surveys and previous data economic factors/wages/energy material availability – whether the materials and subassemblies can be sourced at a rate to keep up with the production rate. The reliance on 'just-in-time' manufacturing manufacturing capacity – the limits imposed by the rate at which a production plant can actually manufacture parts and assemble and ship products commercial backup – the requirement for up-front payments from banks to initiate the production process and produce first batches before any revenue is generated by the sale of these first batches nature of product /number of component parts/assembly – the ease with which the product can be manufactured, assembled, tested, packaged and shipped/complexity of product. Examples/evidence specific product – one/off/batch /high volume specific detail re – economic factors/manufacturing specific commercial requirement.	Level 1 (0-2 marks) Some issues outlined, bullet points (usually focused on one issue) no further or very limited explanation, limited use of examples or supporting evidence. Level 2 (3-5 marks) One or two issues described with some explanation. Appropriate use of technical vocabulary demonstrating a good understanding of concept. Introduction of one example or supporting evidence. Level 3 (6-8 marks) Clear, cogent and well – structured response with two or three issues well explained. Good use of examples and additional evidence to support discussion. Good use of technical vocabulary. Award level 3 for a very detailed, clear response with no examples.	8
		Question	n 7 Total 36

8.	Text	iles				
(Questi	ion	Expected answers	Rationale		Mark
8	(a)		 Give four design requirements for the outdoor jacket shown in Fig.10. Justify each requirement. Function: needs to provide protection from winter weather- warmth /waterproof/breathable Purpose: for casual wear in winter or outdoor pursuits Performance: keep wearer warm/dry/comfortable/be easy to put on/easy to maintain or launder Needs to be available in a range of sizes to fit males and females Aesthetics: needs to be in attractive colour range to suit many tastes Ergonomics: jacket needs to be in arrange of sizes to fit as many people as possible Safety standards: needs to comply with BS and International safety standards for protective wear Fully lined to give added warmth and help with moisture control. 	Clear statement and justification required for a mark. Must be related to product – no marks for generic responses. Four justified design requirements. Give one mark if two valid points given but not fully justified.	4x1	4
	(b)		Describe two examples where ergonomics has influenced the design of the outdoor jacket shown in Fig. 10. Use sketches and/or notes where appropriate. Length of sleeves/length of jacket Velcro fastener on sleeves Position of pocket Length of zip fastening at front Hood shape Adjustable hood Sleeve shape.	brief description detailed description with clear understanding of example 2 marks Two different examples clearly described. Allow reference to given product.	2x2	4

8. Textiles				
Question	Expected answers	Rationale		Mark
(c)	 Describe two ways in which the design of textile products can be legally protected. Patent gives the designer protection copying of the technical and functional aspects Design rights concerns the rights of the creator unless a third party commissions the work Registered designs give you ownership rights for the appearance of the product, Trademark identifies and distinguishes its products (word/name logo/slogan). 	brief description 1 mark detailed description 2 mark Two ways clearly described Candidates may use examples such as copies of catwalk designs /cheaper mass produced versions of catwalk designs. Designs modified by using cheaper fabrics or making slight adaptations o the design Allow reference to given product.	2x2	4
(d)	Explain two ways in which consumers can be assured that they are purchasing a quality textile product. Quality assurance by: Use of logos that guarantee high standards eg Gortex/ BSI markings International standards eg CE Reputation of a reliable textile manufacturing company Offer of a manufacturer's warranty Customer reviews Try-before-you-buy Paying a premium price for the product The use of quality materials in the product.	Allow credit for each if candidate refers to BSI and CE standards in each part. Full credit if candidate has identified the difference between these (UK and Europe). Statement 1 mark Statement explained 1 mark Two quality assurance systems clearly explained.	2x2	4

8. Textiles				
Question	Expected answers	Rationale		Mark
(e) (i)	State one suitable specific fibre for the outdoor jacket shown in Fig. 10. Give two performance characteristics that make the fibre suitable for this use. Fabric	1x1 mark Must state the name of the fibre.	1	
	 Polyester Polyamide Flourofibre (Gortex) Sympatex Cotton/nylon with a waterproof finish. Properties or characteristics	2x1 mark for any of two of the points listed. Award 1 mark for other appropriate point.	2x1	
	Polyester and Polyamide: Insulation. Microfibres trap air Do not absorb water Easy to wash and dry/ Strong have excellent abrasion resistance Good elasticity so recover from creases easily Resistant to moulds Dye well Can be soft and lightweight Microfibres can produce a 'breathable' fabric. Flourofibre (Gore-tex) Gortex is a laminate of an outer fabric, layer of Gore-tex (Flourofibres)membrane and an inner fabric Flourfibres are: Chemically resistant to water Undyeable and so are used to laminate other fibres Windproof Stain resistant Breathable in a micro porous film.			3

8. Textiles				
Question	Expected answers	Rationale		Mark
	Expected answers An open ended zip is used to fasten the front of the outdoor jacket to be manufactured as a batch of 5. Describe, in detail, how to insert the zip fastener and secure the lining. Use a flowchart and/or annotated diagrams to support your answer. Insert the zip On both front edges turn under the seam allowance at the centre front Turn up the hem allowance and tack in place Place the folded front edge of the centre front about 3mm from the zip teeth to allow for the puller to move. Place the bottom of the zip at the hem edge Using the zip foot, machine the zip in place. Start with the zip open. Stitch to the end of the zip and on the right side stitch through the baffles as well. Repeat the process with the left side Once the zip is machined in place check that the hems line up. The zip should open completely. Secure the lining The lining can be secured in two ways It can be hand stitched directly on to the zip by slip hemming or Machined to the zip and then the whole lining is 'bagged out' (turned inside out).	Rationale Level 1 (0-2 marks) Some stages outlined (up to 2), very limited description. Level 2 (3-4 marks) Key stages presented, reasonably well described with key features identified. Level 3 (5-6 marks) Process fully described, key features and technical details identified, Answer must include detail of scientific principles for full marks. To achieve full marks, the described process must be relevant for the batch size. Award maximum of Level 1 if an inappropriate process for the product (or the batch number) is described. Quality of description and communication Basic drawings/chart with limited knowledge 1 mark Good detail with main features identified and labelled 2 marks Detailed clear drawings/chart 3 marks Award full 3 marks if candidate demonstrates good communication. NB A sequence of manufacturing stages can be given in place of a flowchart. Hem edge	6	Mark 9
		Hem edge		

8. Textiles			
Question	Expected answers	Rationale	Mark
		Open ended zip	

8. Textiles					
Question	Expected answers	Rationale	Mark		
(f)	Discuss the factors that influence scale of production of textile products. Issues Demand/quantity of products to be produced economic factors/wages/energy material availability/ seasonal products/fashion trends manufacturing capacity of equipment commercial backup available nature of product/skill level required results of small scale factory trial /complexity of product. Examples/evidence specific product – one off – couture/bespoke batch – fashion clothing high volume – utility clothing /bedding /vests/uniform specific detail re – economic factors/manufacturing specific commercial requirements Use of JIT to respond to fashion trends.	Level 1 (0-2 marks) Some issues outlined, bullet points (usually focused on one issue) no further or very limited explanation, limited use of examples or supporting evidence. Level 2 (3-5 marks) One or two issues described with some explanation. Appropriate use of technical vocabulary demonstrating a good understanding of the concept. Introduction of one example or supporting evidence. Level 3 (6-8 marks) Clear, cogent and well – structured response with two or three issues well explained. Good use of examples and additional evidence to support discussion. Good use of technical vocabulary. Award level 3 for a very detailed, clear response with no examples.	8		
	Question 8 Total 36				

OCR (Oxford Cambridge and RSA Examinations)
1 Hills Road
Cambridge
CB1 2EU

OCR Customer Contact Centre

14 – 19 Qualifications (General)

Telephone: 01223 553998 Facsimile: 01223 552627

Email: general.qualifications@ocr.org.uk

www.ocr.org.uk

For staff training purposes and as part of our quality assurance programme your call may be recorded or monitored

Oxford Cambridge and RSA Examinations is a Company Limited by Guarantee Registered in England Registered Office; 1 Hills Road, Cambridge, CB1 2EU Registered Company Number: 3484466 OCR is an exempt Charity

OCR (Oxford Cambridge and RSA Examinations) Head office

Telephone: 01223 552552 Facsimile: 01223 552553

