



ASSESSMENT and
QUALIFICATIONS
ALLIANCE

Mark scheme

June 2002

GCE

Physics B

Unit PHB6

Copyright © 2002 AQA and its licensors. All rights reserved.

The Assessment and Qualifications Alliance (AQA) is a company limited by guarantee registered in England and Wales 3644723 and a registered charity number 1073334
Registered address: Addleshaw Booth & Co., Sovereign House, PO Box 8, Sovereign Street, Leeds LS1 1HQ
Kathleen Tattersall: *Director General*

Unit 6: Practical Exercises

Notes for guidance

Letters are used to distinguish between different types of marks in the scheme.

M indicates OBLIGATORY METHOD MARK

This is usually awarded for the physical principles involved, or for a particular point in the argument or definition. It is followed by one or more accuracy marks which cannot be scored unless the M mark has already been scored.

C indicates COMPENSATION METHOD MARK

This is awarded for the correct method or physical principle. In this case the method can be seen or implied by a correct answer or other correct subsequent steps. In this way an answer might score full marks even if *some* working has been omitted.

A indicates ACCURACY MARK

These marks are awarded for correct calculation or further detail. They follow an M mark or a C mark.

B indicates INDEPENDENT MARK

This is a mark which is independent of M and C marks.

Note: Where a correct answer only (c.a.o.) is required, this means that the answer must be as in the Marking Scheme, including significant figures and units.

Where an error carried forward (e.c.f.) is allowed by the Marking Scheme for an incorrect answer, e.c.f. must be written on the script if an error has been carried forward.

Instructions to Examiners

- 1 Give due credit to alternative treatments which are correct. Give marks for what is correct; do not deduct marks because the attempt falls short of some ideal answer. Where marks are to be deducted for particular errors specific instructions are given in the marking scheme.
- 2 Do not deduct marks for poor written communication. Refer the script to the Awardsmeeting if poor presentation forbids a proper assessment. In each paper candidates may be awarded up to two marks for the Quality of Written Communication in cases of required explanation or description. However, no candidate may be awarded more than the total mark for the paper. Use the following criteria to award marks:
 - 2 marks: Candidates write with almost faultless accuracy (including grammar, spelling and appropriate punctuation); specialist terms are used confidently, accurately and with precision.
 - 1 mark: Candidates write with reasonable and generally accurate expression (including grammar, spelling and appropriate punctuation); specialist terms are used with reasonable accuracy.
 - 0 marks: Candidates who fail to reach the threshold for the award of one mark.
- 3 An arithmetical error in an answer should be marked A.E. thus causing the candidate to lose one mark. The candidate's incorrect value should be carried through all subsequent calculations for the question and, if there are no subsequent errors, the candidate can score all remaining marks (indicated by ticks). These subsequent ticks should be marked C.E. (consequential error).
- 4 With regard to incorrect use of significant figures, normally a penalty is imposed if the number of significant figures used by the candidate is one less, or two more, than the number of significant figures used in the data given in the question. The maximum penalty for an error in significant figures is **one mark per paper**. When the penalty is imposed, indicate the error in the script by S.F. and, in addition, write S.F. opposite the mark for that question on the front cover of the paper to obviate imposing the penalty more than once per paper.
- 5 No penalties should be imposed for incorrect or omitted units at intermediate stages in a calculation or which are contained in brackets in the marking scheme. Penalties for unit errors (incorrect or omitted units) are imposed only at the stage when the final answer to a calculation is considered. The maximum penalty is **one mark per question**.
- 6 All other procedures, including the entering of marks, transferring marks to the front cover and referrals of scripts (other than those mentioned above) will be clarified at the standardising meeting of examiners.

Exercise 1

(a)(i)	record of L in mm(500 ± 50) and scale reading for centre of the strip to nearest mm (condone 0)	B1	1
(ii)	new scale reading for centre of the strip (any unit) d correct in mm with unit (ie subtracts scale readings) repeat and average of loaded readings	M1 A1 B1	3
(b)(i)	graph of $\log d$ against $\log L$ is a straight line if the relationship is correct equation $\log d = n \log L + \log k$ stated clearly (condone \ln) n is gradient of the graph or n can be determined from the gradient of the graph $\log k$ and/or k obtainable from intercept or using coordinates substitute in given or log equation NOT k is the intercept	B1 B1 B1 B1	4
(ii)	at least four further measurements for L and d at least 5 with depressions ≥ 10 mm repeat and averages for d record of loaded positions for each L repeat readings for L all readings for L in mm all readings of d in mm (condone 1 dp in averages but must be consistent) all units in table correct ; allow even if L in cm; for log allow $\log(L/\text{mm})$ or $\log L$ (where L is in mm) or $\log(L \text{ in mm})$ not $\log L/\text{mm}$ or $\log L (\text{mm})$ logs in table determined correctly to 2/3 dp (i.e. 2/3 sf in the mantissa) (allow ecf if L is given in cm) (check one line –indicate c) good tabulation of data for $d, L, \log d$ and $\log L$ no split tables; separate columns for observations if in the table; clear presentation with no ambiguous figures(condone one slip)	B2 B1 B2 B1 B1 B1 B1 B1 B1 B1	12
(iii)	knife edges/sharper/thinner to define ends or L clearly use longer strip produce greater range of L or to increase d	use vernier callipers/trav microscope to measure d more accurately use string to support the mass to distribute load evenly or prevent twisting	M1 A1 M1 A1
	not: use a pointer; mark position of centre; use of spirit level		

(c)(i)	labels shown $\log d$ and $\log L$ (ignore units here) or other correct alternative	B1	
	suitable scale points occupying at least $\frac{1}{2}$ the paper in each direction	M1	
	scale not multiples of three		
	plotting accurate; At least 5 points plotted; check 2 randomly	A1	
	best line through the points	B1	
	care in presentation	B1	5
(ii)	conclusion correct for data obtained	B1	1
	e.g. points lie close to straight line so relationship is supported		
	line of best fit is a straight line		
	a straight line fits closely		
	points suggest a curve so relationship is not supported		
(iii)	large triangle and coordinates or sides read correctly	M1	
	answer 3.0 ± 0.5 (allow $2/3$ sf)	A1	2
(iv)	appropriate method to find k	M1	
	read $\log k$ from intercept; find antilog (condone error due to false origin)		
	substitute coordinates of a point in $\log d = n \log L + \log k$		
	use coordinates of d and L substitute in $d = kL^n$		
	(may be from table for this mark)		
	correct manipulation of data (allow $2/3$ sf but ignore unit)	A1	2
	($\log d$ and $\log L$ or d and L must be determined from coordinates on the graph line or correct intercept must be used)		
(d)(i)	higher Young modulus leads to lower depression	B1	1
(ii)	Young modulus is measure of stiffness	C1	
	or related to stretching of materials		
	or $E = \text{stress/strain}$		
	higher Young modulus means it is harder to stretch	A1	
	or will be stiffer		
	or high E means strain smaller for a given stress (or vice versa)		
	lower part of strip is in tension	B1	3
	or top part is in compression		
(iii)	substitutions in equation correct in mm(e.c.f.)	M1	
	value for E to 2 or 3 sig figs with unit (Pa or N m^{-2})	A1	2
	if 10^6 used answer is $\frac{1520}{\text{their } k}$; if 10^{-6} used answer is $\frac{1.52 \times 10^{-9}}{\text{their } k}$		
(iv)	uncertainty = $3 \times \% \text{ uncertainty in } t + \text{uncertainty in } b + \text{uncertainty in } 1.23$	B1	1
	or uses highest values/lowest values (gives 28%) or vice versa (gives 21%)		
	Accept 23 – 25% provided method correct (condone sfs)		

Total **39**

(b)(i)	values for current (1.1 to 1.3 A) and length of wire in the field (≈ 50 mm) allow if seen in equation; condone length in mm or cm	M1	
	force = (candidate's displacement) $\times 1.4 \times 10^{-4}$ N	M1	
	value for B unit essential	A1	3
(ii)	uncertainty in L ± 1 or ± 2 mm	B1	
	uncertainty in displacement = ± 1 or 2 mm	B1	
	uncertainty in I ± 0.1 or ± 0.01 or ± 0.05 A	B1	
		Max	2
(iii)	uncertainty in B consistent with their (ii)	B1	1
	e.g. = $(F)14\% + d$ (e.g. 10%) + $(I)8\% + (L)2\% = 34\%$		
	Adds all their uncertainties (there must be at least 3 components)		
	may use highest/lowest approach		

Question 2

(19 marks)

- (a)(i) ball compresses on impact B1
 work is done in compressing the ball or block B1
 the ball and/or block becomes warmer or gains internal energy B1
 mention of one other energy transfer or cause of ke loss B1 **3**
 e.g. ke of air particles (condone sound); air resistance **max**
- (ii) measurements of initial and final maximum displacements to nearest mm B1
 must be explicit
 calculates either (initial amplitude)² or (final amplitude)² B1
 energy lost \propto difference in amplitude² M1
 percentage energy lost = $\frac{(A_I^2 - A_F^2)}{A_I^2} \times 100$ using candidate's values A1 **4**
- OR (instead of last two marks)**
 percentage of energy left = $\frac{A_F^2}{A_I^2} \times 100$ M1
 subtracts from 100 A1
- (b)(i) at collision point all energy is kinetic energy B1
 $\frac{1}{2} mv^2 \propto A^2$ (hence $v \propto A$) B1
 or
 $v_{(max)} = 2\pi fA$ B1 **2**
 f constant so (**max**) $v \propto A$ B1
- (ii) measure initial displacement and final displacement B1
 TO for irrelevant measurements: Period OK but not time to hit block
 no use of sensors to measure v
 for at least 5 different initial displacements (allow if measuring h) B1
 $30 \text{ cm} \geq \text{initial displacements} \geq 10 \text{ cm}$ B1
 in $5 \text{ cm} \geq \text{increments} \geq 2 \text{ cm}$ B1
2 max for range etc
 repeat and average for each displacement/measurement
 or take care to avoid parallax errors (allow if measuring h) B1
 plot final displacement against initial displacement which should be a straight line B1
 through the origin if hypothesis is correct **Max 5**
 or determine ratios of displacements which should be the same
 (allow if measuring h) (allow final v against initial v if method for v correct.)
at least 3 marks for physics + use of Physics is accurate, the answer is fluent/well argued with few errors in spelling, punctuation and grammar 2
at least 1 mark for physics + the use of Physics is accurate, but the answer lacks coherence or spelling, punctuation and grammar are poor 1
 the use of Physics is inaccurate, the answer is disjointed, with significant errors in spelling, punctuation and grammar 0
Max 2

- (c) ratio would be lower B1
- more energy would be lost (on collision) or ratio higher since less energy loss B1
- polystyrene: deforms due to collision or deforms plastically or is less elastic B1
- or contains lots of air pocket
- not** it is softer or due to damping **3**