



ADVANCED SUBSIDIARY (AS)
General Certificate of Education
2015

Physics
Assessment Unit AS 3
assessing
Practical Techniques
Session 1
[AY131]

FRIDAY 15 MAY, MORNING

**MARK
SCHEME**

Subject-specific Instructions

In numerical problems, the marks for the intermediate steps shown in the mark scheme are for the benefit of candidates who do not obtain the final correct answer. A correct answer and unit, if obtained from a valid starting-point, gets full credit, even if all the intermediate steps are not shown. It is not necessary to quote correct units for intermediate numerical quantities.

Note that this “correct answer” rule does not apply for formal proofs and derivations, which must be valid in all stages to obtain full credit.

Do not reward wrong physics. No credit is given for consistent substitution of numerical data, or subsequent arithmetic, **in a physically incorrect equation**. However, answers to subsequent stages of questions that are consistent with an earlier incorrect numerical answer, and are based on physically correct equation, must gain full credit. Designate this by writing **ECF** (Error Carried Forward) by your text marks.

The normal penalty for an arithmetical and/or unit error is to lose the mark(s) for the answer/unit line. Substitution errors lose both the substitution and answer marks, but 10^n errors (e.g. writing 550 nm as 550×10^{-6} m) count only as arithmetical slips and lose the answer mark.

Section A

AVAILABLE MARKS

- 1 (a) (i) Length = 15.0 cm approx given to ± 1 mm [1]

- (ii) typical results

Mass/g	New length/cm	Increase in length/cm consistent with their values
200	18.6	3.6
300	19.2	4.2
400	21.0	6.0

[−1] not increasing

[1]

- (b) (i) Yes/No plus explanation consistent with **results**. [1]

- (ii) Uncertainty = ± 0.2 cm (or 0.4 cm) [1]

(Uncertainty in each reading is 0.1 cm (or 0.05 cm)). Therefore the uncertainty in extension is addition of two measurement uncertainties.

Accept larger uncertainties with parallax explanation holding rule [2]

$\curvearrowleft \leq \pm 2$ cm

5

- 2 (a) (i)
- | | Focal length/cm | |
|-------------------------|-----------------|------|
| lens/mirror combination | 10.1 | 1 dp |
- $8.0\text{ cm} \leq f \leq 12.0\text{ cm}$ [1]

- (ii) u and v value recorded, $u < v$ [1]

f consistent with u and v (ignore sig.fig.) [1]

(first value assumed to be u if not stated otherwise) [2]

- (b) % difference = difference/either focal length, e.g. $100 = 0.2/10.1 \times 100$ [1]

Ans consistent with correct substitution [1]

[2]

5

- 3 (a)
- | Mass/g | Time for 10 oscillations/s | | | T/s |
|--------|----------------------------|------|------|------|
| | 1 | 2 | tav | |
| 200 | 5.72 | 5.68 | 5.70 | 0.57 |
| 300 | 6.97 | 6.98 | 6.98 | 0.69 |
| 400 | 8.05 | 8.22 | 8.14 | 0.81 |

- (i) Multiple oscillation \rightarrow time s ≥ 5 s

Headings + units for one heading only

[1]

- (ii) Repetition

[1]

- (iii) Values of T given to 0.01 s

[1] [3]

- (b) (i) $T = Am$ eqn 1

$$T = Am^{\frac{1}{2}} \quad \text{eqn 2} \quad \times$$

$$T = \frac{A}{m} \quad \text{eqn 3} \quad \square$$

[1]

- (ii) Can't be 1 as m doubles T does not

Can't be 3 as m increases so does T

Therefore must be 2

or calculation to support

[1] [2]

5

- 4 (a) (i) Workable circuit with ammeter, voltmeter and PSU and correct PSU polarity. [1]

AVAILABLE MARKS

(ii)

Voltage/V	Current/mA
0	0
0.2	0
0.6	0
1.0	0
1.3	0
1.8	19.6

[0]

values increasing

[2]

- (b) (i) Need to take more readings/just before the first non-zero reading to find exact voltage (at which the led switches on or current $\neq 0$) [1]

- (ii) Switch on voltage = 1.75V (typical) – consistent with Table 4.1 [1]

5

Section A

20

Section B

			AVAILABLE MARKS																			
5	(a) (i)	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Rear Gear R</th><th>G when F = 44</th><th>G when F = 52</th></tr> </thead> <tbody> <tr><td>14</td><td>2.2</td><td>2.6</td></tr> <tr><td>17</td><td>1.8</td><td>2.1</td></tr> <tr><td>20</td><td>1.5</td><td>1.8</td></tr> <tr><td>24</td><td>1.3</td><td>1.5</td></tr> <tr><td>28</td><td>1.1</td><td>1.3</td></tr> </tbody> </table>	Rear Gear R	G when F = 44	G when F = 52	14	2.2	2.6	17	1.8	2.1	20	1.5	1.8	24	1.3	1.5	28	1.1	1.3	[1] per column	
Rear Gear R	G when F = 44	G when F = 52																				
14	2.2	2.6																				
17	1.8	2.1																				
20	1.5	1.8																				
24	1.3	1.5																				
28	1.1	1.3																				
				[2]																		
		[−1] penalty d.p. violation																				
	(ii)	Mention of at least one set of doubles/6 different values (2.6,(2.2,2.1), 1.8, 1.5, 1.3, 1.1)	[1]																			
		There are three sets of double readings and one set which is very close. Allow ECF for wrong data*	[1]	[2]																		
		2.1/2.2 Candidates must state 4 pairs of data for [2] Other errors in Table 5.1 ECF max [1]																				
	(b) (i)	Scales ([−1] if either axis starts from 0) Points plotted ([−1] for each error) Straight line	[2] [2] [1]	[5]																		
	(ii)	Gradient = $40/2.7 = 14.8 \pm .2$ Large Δ +subs Value	[1] [1]	[2]																		
	(iii)	$\omega = 14.8 \times 16.94/\pi$ (consistent with their = 79.8 slope value) Use of values from table 5.2, max [1]	subs ans	[1] [1] [2]																		
	(c) (i)	$G = \frac{0.58 \times 52}{14}$ subs $G = 2.2$	[1] [1]	[2]																		
	(ii)	31.4 (km h^{-1}) approx consistent with their values		[1]																		
	(iii)	$38.1 = \frac{\pi}{16.94} (2.2) \omega$ subs $\omega = 93.4$	[1] [1]	[2]																		
	(d)	0.042 h 2.5 min	[1] [1]	[2]																		
				20																		
			Section B	20																		
			Total	40																		