

General Certificate of Education

Mathematics 6360

MM2B Mechanics 2B

Mark Scheme

2007 examination - June series

Mark schemes are prepared by the Principal Examiner and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation meeting attended by all examiners and is the scheme which was used by them in this examination. The standardisation meeting ensures that the mark scheme covers the candidates' responses to questions and that every examiner understands and applies it in the same correct way. As preparation for the standardisation meeting each examiner analyses a number of candidates' scripts: alternative answers not already covered by the mark scheme are discussed at the meeting and legislated for. If, after this meeting, examiners encounter unusual answers which have not been discussed at the meeting they are required to refer these to the Principal Examiner.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of candidates' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Further copies of this Mark Scheme are available to download from the AQA Website: www.aqa.org.uk

Copyright © 2007 AQA and its licensors. All rights reserved.

COPYRIGHT

AQA retains the copyright on all its publications. However, registered centres for AQA are permitted to copy material from this booklet for their own internal use, with the following important exception: AQA cannot give permission to centres to photocopy any material that is acknowledged to a third party even for internal use within the centre.

Set and published by the Assessment and Qualifications Alliance.

М	mark is for method				
m or dM	mark is dependent on one or more M marks and is for method				
А	mark is dependent on M or m marks and is for accuracy				
В	mark is independent of M or m marks and is for method and accuracy				
E	mark is for explanation				
or ft or F	follow through from previous				
	incorrect result	MC	mis-copy		
CAO	correct answer only	MR	mis-read		
CSO	correct solution only	RA	required accuracy		
AWFW	anything which falls within	$\mathbf{F}\mathbf{W}$	further work		
AWRT	anything which rounds to	ISW	ignore subsequent work		
ACF	any correct form	FIW	from incorrect work		
AG	answer given	BOD	given benefit of doubt		
SC	special case	WR	work replaced by candidate		
OE	or equivalent	FB	formulae book		
A2,1	2 or 1 (or 0) accuracy marks	NOS	not on scheme		
–x EE	deduct x marks for each error	G	graph		
NMS	no method shown	с	candidate		
PI	possibly implied	sf	significant figure(s)		
SCA	substantially correct approach	dp	decimal place(s)		

Key to mark scheme and abbreviations used in marking

No Method Shown

Where the question specifically requires a particular method to be used, we must usually see evidence of use of this method for any marks to be awarded. However, there are situations in some units where part marks would be appropriate, particularly when similar techniques are involved. Your Principal Examiner will alert you to these and details will be provided on the mark scheme.

Where the answer can be reasonably obtained without showing working and it is very unlikely that the correct answer can be obtained by using an incorrect method, we must award **full marks**. However, the obvious penalty to candidates showing no working is that incorrect answers, however close, earn **no marks**.

Where a question asks the candidate to state or write down a result, no method need be shown for full marks.

Where the permitted calculator has functions which reasonably allow the solution of the question directly, the correct answer without working earns **full marks**, unless it is given to less than the degree of accuracy accepted in the mark scheme, when it gains **no marks**.

Otherwise we require evidence of a correct method for any marks to be awarded.

MM2B	r	1		
Q	Solution	Marks	Total	Comments
1(a)	Kinetic energy = $\frac{1}{2} \times 5 \times 10^2$	M1		Full method
	= 250 J	A1	2	
(b)	Using conservation of energy: KE when box hits ground			
	= Initial KE + Change in potential energy	M1		Could have sign errors
	$= 250 + 5 \times 30 \times g$	Alft		
	= 1720 J	A1	3	AG; SC2 $5 \times 35.1 \times g = 1720$
(c)	$\frac{1}{2}mV^2 = 1720$	M1		
(0)	2			
	$V^2 = 688$	A1		
	$V^2 = 688$.:. Speed is 26.2 m s ⁻¹	A1	3	CAO; accept $\sqrt{688}$ or $4\sqrt{43}$; SC2 26.3
(d)	No air resistance	E1		Or no resistance forces
	Box is a particle	E1	2	Deduct 1 mark for unacceptable third reason
	Total		10	
2(a)	Symmetry of the lamina about PQ	E1	1	Accept 'mirror line'
(b)	Taking moments about <i>AB</i> :			
(~)	$600\rho \times 15 + 100\rho \times 35$	M1A1		Condone lack of ρ
	$=700\rho\overline{x}$	A1		,
	$\overline{x} = 17.857 = 17.9 \text{ cm}$	A1	4	SC3 17.8
(c)	$\tan\theta = \frac{10}{17.857}$	M1A1		M1 for use of $\tan \theta$
	= 0.56			
	Angle is 29.2488	M1		
	= 29°	A1	4	
	Total		9	

<u>12B (con</u>			m	C
Q	Solution	Marks	Total	Comments
3(a)	Using $F = ma$:			
	$2400\mathbf{i} - 4800t\mathbf{j} = 800\mathbf{a}$	M1		
	$\mathbf{a} = 3\mathbf{i} - 6t\mathbf{j}$	A1	2	
(h)	$\mathbf{v} = \int \mathbf{a} \mathrm{d}t$	M1		
(0)				
	$= 3t\mathbf{i} - 3t^2\mathbf{j} + \mathbf{c}$	A1		Condone no '+ \mathbf{c} '
	When $t = 0$, $v = 6i + 30j$			
	$\therefore \mathbf{c} = 6\mathbf{i} + 30\mathbf{j}$	M1		Needs '+ \mathbf{c} ' above
	$\therefore \mathbf{v} = (3t+6)\mathbf{i} + (30-3t^2)\mathbf{j}$	A1	4	AG
(c)	$\mathbf{r} = \int \mathbf{v} \mathrm{d}t$	M1		
(0)	-	1011		
	$= (\frac{3}{2}t^{2} + 6t)\mathbf{i} + (30t - t^{3})\mathbf{j} + \mathbf{d}$	A1,A1		A1 i term, A1 j term; condone no '+ \mathbf{d} '
	$\frac{1}{2}$	111,111		Tri i termi, Tri j termi, condone no 🖓 u
	When $t = 0$, $\mathbf{r} = 2\mathbf{i} + 5\mathbf{j}$			
	\therefore d = 2i + 5j	M1		
	:. $\mathbf{r} = (\frac{3}{2}t^2 + 6t + 2)\mathbf{i} + (30t - t^3 + 5)\mathbf{j}$		-	
	$\therefore \mathbf{r} = (-t^{2} + 6t + 2)\mathbf{i} + (30t - t^{2} + 5)\mathbf{j}$	A1	5	
	Total		11	
4(a)	Centre of mass of rod is 3 m from river	B1		Use of centre of mass is centre of rod
	bank			
	Taking moments about A, edge of bank:			Or resolve $R = 65g$
	$3 \times 15 = 50x$	M1		Moments about any point (correct) M
	x = 0.9	A1	3	0.9 A
			U U	
(b)	Taking moments about A:			
(0)	$50 \times 2 = 15 \times 3 + m \times 8$	M1A1		M1 3 terms, 2 correct
	55 = 8m	A1		
		AI		
	$m = 6\frac{7}{8}$			
	8			
	7 .	A1	4	Accept 6.88 and 6.87
	Mass is 6-kg		- T	
	Mass is $6\frac{7}{8}$ kg	AI		*
	Mass is $6\frac{1}{8}$ kg	AI		
(c)	Mass is $6\frac{1}{8}$ kg Centre of mass of rod is 3 m from river	E1	1	Centre of mass is at centre of rod
(c)	0			
(c)	Centre of mass of rod is 3 m from river			
	Centre of mass of rod is 3 m from river bank	E1		
(c) (d)	Centre of mass of rod is 3 m from river bank eg Woman is a particle		1	
	Centre of mass of rod is 3 m from river bank	E1	1	

Q	Solution	Marks	Total	Comments
5(a)	Using conservation of energy (lowest and highest points):	M1		
	$\frac{1}{2}m(7v)^2 = \frac{1}{2}mv^2 + 2mga$	A1A1		A1 for $7v$ and v
	$\frac{48}{2}v^2 = 2ga$	M1		Needs 48 or 24
	$\therefore v = \sqrt{\frac{ag}{12}}$	A1	5	AG
(b)	Velocity at A is $\sqrt{\frac{ag}{12}}$			
	Resolving vertically at A:	M1		3 terms
	$m\frac{v^2}{a} + R = mg$	A1,A1		A1 correct 3 terms, A1 correct signs
	$R = mg - \frac{m}{a} \times \frac{ag}{12}$			$\left(1-\frac{1}{12}\right)mg$ M1A2
	$=\frac{11}{12}mg$	A1	4	Condone $-\frac{11}{12}mg$
	Total		9	
6(a)	EPE is $\frac{\lambda x^2}{2l}$			
	$=\frac{200(0.5)^2}{2\times 2}$	M1		
	2×2 = 12.5 J	A1	2	
(b)	When string becomes slack,			
	using $\frac{1}{2}mv^2 = \text{loss in EPE}$:	M1		NB Using $\sqrt{5}$ to answer (a) and thus (b \Rightarrow no marks
	$\frac{1}{2} \times 5 \times v^2 = 12.5$	A1		
	2 Speed is $\sqrt{5}$ m s ⁻¹	A1	3	AG
(c)	Resolving vertically, $R = 5g$	B1		
	$F = \mu R$	M1		
	$0.4 \times 5g = 2g$	M1		
	Using change in energy = work done: $2g \times 0.5 =$	M1		M1 for force \times distance
	$\frac{1}{2} \times 5 \times \left(\sqrt{5}^2\right) - \frac{1}{2} \times 5 \times v^2$	A1,A1		A1 first term (or 12.5) A1 second term (inc $-$)
	$9.8 = 12.5 - \frac{5}{2}v^2$			
	$v^2 = 1.08$			
	Speed is 1.04 m s ⁻¹	A1	7	
	Total		12	

MM2B (con	t)			
Q	Solution	Marks	Total	Comments
7(a)	Using $F = ma$:			
	$-\lambda mv = ma = m \frac{\mathrm{d}v}{\mathrm{d}t}$	M1		Condone no '-'
	$-\lambda mv = ma = m\frac{\mathrm{d}v}{\mathrm{d}t}$ $\therefore \frac{\mathrm{d}v}{\mathrm{d}t} = -\lambda v$	A1	2	AG Note: no use of $m \Rightarrow$ no marks in (a)
(b)	$\int \frac{dv}{v} = -\lambda \int dt$ ln v = -\lambda t + c v = C e^{-\lambda t}	M1		
	$\ln v = -\lambda t + c$ $v = C e^{-\lambda t}$	A1		Needs '+ c '
	When $t = 0$, $v = U \implies C = U$ $v = U e^{-\lambda t}$	M1 A1	4	Needs correct working AG
	<u>v = 0 c</u> Total		6	
8 (a)	Q is in equilibrium	E1	U	<i>Q</i> at rest, or not moving
o(a)	T = 5g = 49 N	B1	2	AG
	Resolving vertically for <i>P</i> : $T \cos \theta = 3g$ $\cos \theta = \frac{3}{5}$ $\theta = \cos^{-1}\frac{3}{5} = 53.1^{\circ}$	M1A1		
	$\theta = \cos^{-1}\frac{3}{5} = 53.1^{\circ}$	A1	3	Do not condone 53°
(c)	$\therefore \sin \theta = \frac{4}{5}$	B1		
	Resolving horizontally for <i>P</i> : $\frac{mv^2}{r} = T \sin \theta$ $3v^2 = 4$	M1A1		M1 2 terms: 1 term correct, other term includes sin or cos
	$\frac{3v^2}{r} = \frac{4}{5} \times 5g$ $\frac{3 \times 4^2}{r} = 4g$			
	$r = \frac{48}{4g}$			
	= 1.22	A1	4	SC3 1·23
			9	
	TOTAL		75	