




Question Number	Scheme	Marks
1. (a)	$\text{CLM: } 2000 \times 10 = 2000v + 3000 \times 5$ $v = 2.5 \text{ m s}^{-1}$	M1, A1 B1 (3)
(b)	$I = 3000 \times 5 \text{ (or } 2000(10 - 2.5))$ $= 15000 \text{ Ns}$	M1 A1 (2) (5 marks)
2. (a)	 <p>$R(\uparrow) 8 = 12 \cos \beta \text{ or } 12 \sin \alpha$ $\Rightarrow \beta = 41.8^\circ \text{ or } \alpha = 48.2^\circ$ $\Rightarrow \theta = 138.2^\circ$</p>	M1 A1 A1 (3)
(b)	$R(\rightarrow) X = 12 \cos 41.8^\circ \text{ (or } 12 \sin 48.2^\circ)$ $= 8.94$	M1 A1ft A1 (3) (6 marks)
3. (a)	$\mathbf{a} = [-14\mathbf{i} + 21\mathbf{j} - (6\mathbf{i} - 27\mathbf{j})] \div 4$ $= (-5\mathbf{i} + 12\mathbf{j}) \text{ m s}^{-2}$	M1 A1 A1 (3)
(b)	$ \mathbf{a} = \sqrt{(5^2 + 12^2)} = 13$ $ \mathbf{F} = m \mathbf{a} = 0.4 \times 13 = 5.2 \text{ N}$	M1 M1 A1 (3) (6 marks)
Alt (b)	$\mathbf{F} = 0.4(5\mathbf{i} + 12\mathbf{j}) = 2\mathbf{i} + 4.8\mathbf{j}$ $ \mathbf{F} = \sqrt{(2^2 + 4.8^2)} = 5.2 \text{ N}$	M1 M1 A1 (3)

Question Number	Scheme	Marks
4. (a) $\mathbf{p} = 10t\mathbf{j}$ $\mathbf{q} = (6\mathbf{i} + 12\mathbf{j}) + (-8\mathbf{i} + 6\mathbf{j})t$		B1 M1 A1 (3)
(b) $t = 3: \mathbf{p} = 30\mathbf{j}, \mathbf{q} = -18\mathbf{i} + 30\mathbf{j}$ \Rightarrow dist. apart = 18 km		M1 A1 A1 (3)
Alt. (b) $\mathbf{PQ} = \mathbf{q} - \mathbf{p} = (6 - 8t)\mathbf{i} + (12 - 4t)\mathbf{j}$ $t = 3: \mathbf{PQ} = -18\mathbf{i} + 0\mathbf{j}$ Dist. = 18 km	$ \text{ or } \mathbf{PQ} ^2 = (6 - 8t)^2 + (12 - 4t)^2$ $t = 3 \rightarrow \mathbf{PQ} = 18$	M1 A1 A1 A1
(c) Q north of $P \Rightarrow 6 - 8t = 0$ $t = \frac{3}{4}$		M1 A1 (2)
		(8 marks)
5.	 <p>$R(\nearrow): T \cos 20^\circ = F + 1.5g \sin 30^\circ$ $R(\nwarrow): T \sin 20^\circ + R = 1.5g \cos 30^\circ$ Using $F = \frac{1}{3}R$ Eliminating R, solve T $T = 11$ or 11.0 N</p>	M1 A2,1,0 M1 A2,1,0 M1 M1, M1 A1 (10 marks)
6.	 <p>(a) $M(A): Wx + 120 \times 1.5 = R \times 2 + 2R \times 1$ $R(\uparrow) 3R = W + 120$ Hence $Wx + 180 = 3R = W = 120$ $W(1 - x) = 60$ $W = \frac{60}{1 - x}$</p>	M1 A2, 1, 0 M1 A1 M1 A1 M1 A1cso (8)
(b) $W > 0 \Rightarrow x < 1$		M1 A1 (2)

(10 marks)

Question Number	Scheme	Marks
7. (a)	$v^2 = u^2 + 2as: \quad 0 = u^2 - 2 \times 9.8 \times 25.6$ $u^2 = 501.76 \Rightarrow u = 22.4 \text{ } (\star)$	M1 A1 A1cso (3)
(b)	$-1.5 = 22.4T - 4.9T^2$ $4.9T^2 - 22.4T - 1.5 = 0$ $T = \frac{22.4 \pm \sqrt{22.4^2 + 4 \times 1. \times 4.9}}{9.8}$ $= 4.64 \text{ s}$	M1 A1 M1 M1 A1 (4)
(c)	Speed at ground $v = 22.4 - 9.8 \times 4.64$ $v = -23.07$ (or $v^2 = 22.4^2 + 2 \times 9.8 \times 1.5, \quad v = 23.05$) $v^2 = u^2 + 2as: \quad 0 = 23.07^2 + 2 \times a \times 0.025$ ($\rightarrow a = -10644.5$) $F - 0.6g = 0.6a$ $F = 6390 \text{ N } (3 \text{ sf})$	M1 A1 M1 A1ft M1 A1 A1 (6)
(d)	Air resistance; variable F ;	B1 (1) (14 marks)

Question Number	Scheme	Marks
8. (a)	<p>A: $T = 0.8a$ B: $1.2g - T = 1.2a$ Solve: $T = 0.48g = 4.7 \text{ N}$</p>	B1 M1 A1 M1 A1 (5)
(b)	<p>$a = 0.6g = 5.88$ Hence $0.6 = \frac{1}{2} \times 0.6g \times t^2$ $t = 0.45 \text{ or } 0.452 \text{ s}$</p> <p>$F = \mu R = \frac{1}{5} \times 0.8g$ A: $T' - F = 0.8a'$ B: $1.2g - T' = 1.2a'$</p> <p>Solve: $a' = 0.52g$ $0.6 = \frac{1}{2} \times 0.52g \times t^2$ $t = 0.49 \text{ or } 0.485 \text{ s}$</p>	M1 M1 A1 (3) B1 M1 A1 B1 M1 A1 M1 A1 (8)
		(16 marks)