MARK SCHEME for the October/November 2011 question paper

MMM. Hiremepapers.com

for the guidance of teachers

9702 PHYSICS

9702/52

Paper 5 (Planning, Analysis and Evaluation), maximum raw mark 30

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

• Cambridge will not enter into discussions or correspondence in connection with these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2011 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



Page 2		Mark Scheme: Teachers' version	Syllabus	Paper				
		GCE AS/A LEVEL – October/November 2011	9702	52				
Planning (15 marks)								
Defining the problem (3 marks)								
P P	Keep the	dependent variable, <i>B</i> is the dependent variable or varia	ry <i>r</i> and measur	e <i>B</i> . [1] [1]				
Ρ		ccept same coil. e current in the coil <u>constant</u> .		[1]				
Me	thods of (data collection (5 marks)						
	Diagram	showing coil and labelled Hall probe positione	d in the cent	re of a coil.				
		s will not be credited.		[1]				
		agram for coil connected to a (<u>d.c.</u>) power supply. Hall probe to voltmeter/c.r.o.		[1]				
WIO		Ivanometer but do not allow ammeter.		[1]				
	Measure	diameter or radius with a ruler/vernier callipers.		[1]				
M5		o locate centre of coil. rmine max $V_{\rm H}$; cross rules; projection		۲4				
	e.y. uele	$\frac{1}{1}$		[1				
Me		nalysis (2 marks)						
A		aph of <i>B</i> against 1/ <i>r</i> [allow lg <i>B</i> against lg <i>r</i> or other vali		[1]				
A		ship is valid if the graph is a straight line passing throug nen straight line with gradient = −1 (ignore reference to		[1]				
0-0								
Sat		derations (1 mark) on linked to (large) heating of <u>coil</u> , e.g. switch of	f when not in	use to avoid				
U		ing coil; do not touch coil because it is hot.		[1]				
A .I.								
D		etail (4 marks) points might include		[4				
1		e current/large number of turns to create a large magne	etic field.	[·				
2	Use of rh	neostat to keep current constant in coil.						
3		constant current with ammeter to check current is cons						
4 5		e at right angles to direction of magnetic field/plane of		aquara fix t				
5		ed method to keep Hall probe in constant orientation cal bench or equivalent).	(e.g. use of set	square, lix to				
6		ortional to voltage across Hall probe/calibrate Hall prob	pe in a known m	agnetic field.				
7	Repeat e	experiment with Hall probe reversed and average.						
8	Repeat r	neasurement for <i>r</i> or <i>d</i> and average.						
Do	not allow	vague computer methods.						

Page 3	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2011	9702	52

2 Analysis, conclusions and evaluation (15 marks)

Part	Mark	Expected Answer	Additional Guidance
(a)	A1	1.5 or 3/2	Ignore <i>y</i> -intercept (incorrect <i>y</i> -intercept will be penalised in (d)(i)).
(b)	T1 T2	8.111 or 8.11064.388.258 or 8 25774.628.625 or 8.62535.188 (5.19)8.827 or 8.82675.483 (5.48)9.029 or 9.02945.771 (5.77)9.274 or 9.27426.152 (6.15)	Allow a mixture of decimal places. T1 must be table values. T2 must be a minimum of 2 d.p. Ignore rounding errors.
	U1	From \pm 0.07 or \pm 0.08, to \pm 0.005	Allow more than one significant figure.
(c) (i)	G1	Six points plotted correctly	Must be within half a small square. Do not allow 'blobs' (more than half a small square). Ecf allowed from table.
	U2	Error bars in lg <i>T</i> plotted correctly	All error bars to be plotted. Must be accurate to less than half a small square.
(c) (ii)	G2	Line of best fit	If points are plotted correctly then lower end of line should pass between (8.0, 4.20) and (8.0, 4.28) and upper end of line should pass between (9.4, 6.32) and (9.4, 6.38). Allow ecf from points plotted incorrectly – examiner judgement.
	G3	Worst acceptable straight line. Steepest or shallowest possible line that passes through <u>all</u> the error bars.	Line should be clearly labelled or dashed. Examiner judgement on worst acceptable line. Lines must cross. Mark scored only if error bars are plotted.
(c) (iii)	C1	Gradient of best fit line	The triangle used should be at least half the length of the drawn line. Check the read offs. Work to half a small square. Do not penalise POT.
	U3	Uncertainty in gradient	Method of determining absolute uncertainty Difference in worst gradient and gradient.
(c) (iv)	C2	Negative <i>y</i> -intercept	Must be negative. FOX does not score. Check substitution into $y = mx + c$. Allow ecf from (c)(iii) .
	U4	Uncertainty in <i>y</i> -intercept	Uses worst gradient and point on WAL. Do not check calculation. FOX does not score.
(d) (i)	C3	Method to determine k	$k=10^{2 \times y-\text{intercept}}$ [k is about 10 ⁻¹⁶ , if FOX 10 ⁸]
	U5	Uncertainty in <i>k</i>	Best k – worst k using y -intercept. Allow ecf for method from (c)(iv) .
(d) (ii)	C4	<i>M</i> between 2.36×10^{26} and 2.36×10^{28} given to 2 or 3 s.f.	Must be in range. Allow between 2.4×10^{26} and 2.4×10^{28} for 2 s.f.

[Total: 15]

Page 4 Mark Scheme: Teachers' version		Syllabus	Paper
	GCE AS/A LEVEL – October/November 2011	9702	52

Uncertainties in Question 2

- (c) (iii) Gradient [E3] Uncertainty = gradient of line of best fit – gradient of worst acceptable line Uncertainty = ½ (steepest worst line gradient – shallowest worst line gradient)
 - (iv) [E4]

Uncertainty = *y*-intercept of line of best fit – *y*-intercept of worst acceptable line Uncertainty = $\frac{1}{2}$ (steepest worst line gradient – shallowest worst line gradient)

(d) (i) [E5] Uncertainty = best *k* –worst *k*