mmn. XtremeRabers.com

CAMBRIDGE INTERNATIONAL EXAMINATIONS

GCE Advanced Subsidiary Level and GCE Advanced Level

MARK SCHEME for the October/November 2012 series

9702 PHYSICS

9702/22

Paper 2 (AS Structured Questions), maximum raw mark 60

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2012 series for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level components and some Ordinary Level components.



		J -		GCE AS/A LEVEL – October/November 2012	9702	22	
1	(a)			<i>D</i> identified as $kg m s^{-2}$ units shown: units for <i>A</i> : m^2 units for v^2 : $m^2 s^{-2}$ units for ρ : $kg m^{-3}$		M1	
		C =	kg m	$\frac{\text{kgms}^{-2}}{\text{m}^{-3} \text{ m}^2 \text{ m}^2 \text{s}^{-2}}$ with cancelling/simplification to give <i>C</i> no	units	A1	[2]
	(b)	(i)	strai	ght line from (0,0) to (1,9.8) ± half a square		B1	[1]
		(ii)	½ m v = ($v^2 = mgh$ or using $v^2 = 2as$ $(2 \times 9.81 \times 1000)^{1/2} = 140 \mathrm{m s^{-1}}$		C1 A1	[2]
	(c)	(i)		yht = drag (<i>D</i>) (+ upthrust) w mg or <i>W</i> for weight and <i>D</i> or expression for <i>D</i> for drag		B1	[1]
		(ii)	1.	$mg = 1.4 \times 10^{-5} \times 9.81$		C1	
				$1.4 \times 10^{-5} \times 9.81 = 0.5 \times 0.6 \times 1.2 \times 7.1 \times 10^{-6} \times v^2$		M1	
				$v = 7.33 \mathrm{m s^{-1}}$		A0	[2]
				line from (0,0) correct curvature to a horizontal line at ve line reaches 7 m s ⁻¹ between 1.5 s and 3.5 s	elocity of 7 m s ⁻¹	M1 A1	[2]
2	(a)	•		t) force = rate of change of momentum / allow proportion in momentum / time (taken)	nal to	В1	[1]
	(b)	(i)	Δp =	: (–) 65 × 10 ⁻³ (5.2 + 3.7)		C1	
			=	= (–) 0.58 N s		A1	[2]
		(ii) $F = 0.58/7.5 \times 10^{-3}$					
			=	= 77(.3) N		A1	[1]
	(c)	(i)		force on the wall from the ball is equal to the force on babut in the opposite direction (statement of Newton's third law can score one mark)	all from the wall	M1 A1	[2]
				momentum change of ball is equal and opposite to mon of the wall / change of momentum of ball and wall is zer	_	B1	[1]
		(ii)		tic energy (of ball and wall) is reduced / not conserved sow relative speed of approach does not equal relative sp		B1	[1]

Mark Scheme

Syllabus

Paper

Page 2

Page 3	Mark Scheme	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2012	9702	22

3 (a) metal: regular / repeated / ordered arrangement / pattern / lattice

or long range order (of atoms / molecules / ions) B1

polymer: <u>tangled</u> chains (of atoms / molecules) or <u>long</u> chains (of

atoms / molecules / ions)

amorphous: disordered / irregular arrangement or short range order (of atoms / molecules / ions) B1 [3]

B1

C₁

- (b) metal: straight line or straight line then curving with less positive gradient B1 polymer: curve with decreasing gradient with steep increasing gradient at end B1 [2]
- 4 (a) waves (travels along tube) reflect at closed end / end of tube incident and reflected waves or these two waves are in opposite directions interfere or stationary wave formed if tube length equivalent to $\lambda / 4$, $3\lambda / 4$, etc.
 - (b) (i) 1. no motion (as node) / zero amplitude B1 [1]
 - vibration backwards and forwards / maximum amplitude along lengthB1 [1]
 - (ii) $\lambda = 330 / 880 (= 0.375 \text{ m})$ C1 $L = 3\lambda / 4$ C1 $L = 3 / 4 \times (0.375) = 0.28 (0.281) \text{ m}$ A1 [3]
- 5 (a) (i) $I_1 = I_2 + I_3$ B1 [1]
 - (ii) I = V/R or $I_2 = 12/10$ (= 1.2A) C1 $R = [1/6 + 1/10]^{-1}$ [total $R = 3.75 \Omega$] or $I_3 = 12/6$ (= 2.0A) C1 $I_1 = 12/3.75 = 3.2$ A or $I_1 = 1.2 + 2.0 = 3.2$ A A1 [3]
 - (iii) power = VI or I^2R or V^2/R

 $x = \frac{\text{power in wire}}{\text{power in series resistors}} = \frac{I_2^2 R_w}{I_3^2 R_s} \text{ or } \frac{V_2}{V_3} \text{ or } \frac{V^2 / R_w}{V_3}$

- $x = 12 \times 1.2 / 12 \times 2.0 = 0.6(0)$ allow 3 / 5 or 3:5 A1 [3]
- (b) p.d. BC: $12 12 \times 0.4 = 7.2$ (V) / p.d. AC = 4.8 (V) C1 p.d. BD: $12 12 \times 4$ / 6 = 4.0 (V) / p.d. AD = 8.0 (V) C1 p.d. = 3.2 V
- 6 (a) extension is proportional to force / load B1 [1]
 - (b) F = mg C1 $x = (mg/k) = 0.41 \times 9.81/25 = (4.02/25)$ M1 $x = 0.16 \,\text{m}$ A0 [2]

	Page 4				Mark	Scheme	Syllabus	Paper	
				GCE A	AS/A LEVEL – C	October/November 2012	9702	22	
	(c)	(i)	weig	ght and (rea	action) force from	m spring (which is equal to te	ension in spring)	B1	[1]
		(ii)			0.06 × 25 = <i>ma</i> 5 = 5.52 (N)	or 0.22 × 25 = 5.5		C1	
			a = (1× 9.81) / 0.41	or 1.5 / 0.41 and (5.5 – 4.02 gives 3.6 m s ⁻²	2)	C1 A1	[3]
	(d)	pot	ential	energy		ergy to kinetic energy and gra		B1 B1	[2]
7	(a)	Ān	umbe	He $\rightarrow \frac{4}{2}$ Heers correcters correct	e + 2 ¹ ₁ p + Q (4 and 1) (2 and 1)			B1 B1	[2]
	(b)	the	two i	•	ive 1 neutron an	nd two neutrons ns but different number of ne	utrons']	B1 B1	[2]
	(c)	ene		- mass	neutron numbe	er		B1 B1 B1	[2]
	(d)	(i)	γ rac	diation				B1	[1]
		(ii)	prod	<u>luct</u> (s) mus	t have kinetic e	nergy		B1	[1]
	(e)	13.	8 Me\	/ = 13.8 × 1.6	1.6 × 10 ⁻¹⁹ × 10 ⁰	⁶ (= 2.208 × 10 ⁻¹²)		C1	
				13.8 × 1.6 2) × 10 ¹³ s ⁻				A1	[2]