GATE 2012 Online Examination AE: AEROSPACE ENGINEERING

Duration: Three Hours

Read the following instructions carefully.

- Student Bounts, com 1. The computer allotted to you at the examination center runs a specialized software that permits only one answer to be selected for multiple choice questions using a mouse. Your answers shall be updated and saved on a server periodically and at the end of the examination.
- 2. To login, enter your Registration Number and password provided in the envelope. Go through the symbols used in the test and understand the meaning before you start the examination. You can view all questions by clicking on the View All Ouestions button in the screen after the start of the examination.
- 3. To answer a question, select the question using the selection panel on the screen and choose the correct answer by clicking on the radio button next to the answer. To change the answer, just click on another option. If you wish to leave a previously answered question unanswered, click on the button next to the selected option.
- 4. The examination will automatically stop at the end of 3 hours
- 5. There are a total of 65 questions carrying 100 marks. Except questions Q.26 Q.30, all the other questions are of multiple choice type with only one correct answer. Questions Q.26 - Q.30 require a numerical answer, and a number should be entered using the virtual keyboard on the monitor.
- 6. Questions Q.1-Q.25 carry 1 mark each. Questions Q.26-Q.55 carry 2 marks each. The 2 marks questions include two pairs of common data questions and two pairs of linked answer questions. The answer to the second question of the linked answer questions depends on the answer to the first question of the pair. If the first question in the linked pair is wrongly answered or is unattempted, then the answer to the second question in the pair will not be evaluated.
- 7. Questions Q.56 Q.65 belong to General Aptitude (GA) section and carry a total of 15 marks. Questions Q.56 – Q.60 carry 1 mark each, and questions Q.61 – Q.65 carry 2 marks each.
- 8. Unattempted questions will result in zero mark and wrong answers will result in **NEGATIVE** marks. There is no negative marking for questions of numerical answer type, i.e., for Q.26 – Q.30. For all 1 mark questions, $\frac{1}{3}$ mark will be deducted for each wrong answer. For all 2 marks questions, $\frac{2}{3}$ mark will be deducted for each wrong answer. However, in the case of the linked answer question pair, there will be negative marks only for wrong answer to the first question and no negative marks for wrong answer to the second question.
- Calculator is allowed. Charts, graph sheets or tables are **NOT** allowed in the examination hall. Do the rough work in the Scribble Pad provided.
- 10. You must sign this sheet and leave it with the invigilators at the end of the examination.

DECLARATION: I hereby declare that I have read and followed all the instructions given in this sheet.

į	Registration Number	AE				
	Name					
	Signature					

Verified that the above entries are correct.	
Invigilator's signature:	

Q. 1 - Q. 25 carry one mark each.

- The constraint $A^2 = A$ on any square matrix A is satisfied for 0.1
 - (A) the identity matrix only.

- (B) the null matrix only.
- (C) both the identity matrix and the null matrix.
- (D) no square matrix A.
- Q.2 The general solution of the differential equation $\frac{d^2y}{dt^2} + \frac{dy}{dt} - 2y = 0$ is
 - (A) $Ae^{-t} + Be^{2t}$ (B) $Ae^{-2t} + Be^{-t}$ (C) $Ae^{-2t} + Be^{t}$ (D) $Ae^{t} + Be^{t}$

- Q.3 An aircraft in trimmed condition has zero pitching moment at
 - (A) its aerodynamic centre.

- (B) its centre of gravity.
- (C) 25% of its mean aerodynamic chord.
- (D) 50% of its wing root chord.
- In an aircraft, constant roll rate can be produced using ailerons by applying Q.4
 - (A) a step input.

(B) a ramp input.

(C) a sinusoidal input.

- (D) an impulse input.
- For a symmetric airfoil, the lift coefficient for zero degree angle of attack is Q.5
 - (A) 1.0
- (B) 0.0
- (C) 0.5
- (D) 1.0
- 0.6 The critical Mach number of an airfoil is attained when
 - (A) the freestream Mach number is sonic.
 - (B) the freestream Mach number is supersonic.
 - (C) the Mach number somewhere on the airfoil is unity.
 - (D) the Mach number everywhere on the airfoil is supersonic.
- Q.7 The shadowgraph flow visualization technique depends on
 - (A) the variation of the value of density in the flow.
 - (B) the first derivative of density with respect to spatial coordinate.
 - (C) the second derivative of density with respect to spatial coordinate.
 - (D) the third derivative of density with respect to spatial coordinate.
- The Hohmann ellipse used as earth-Mars transfer orbit has Q.8
 - (A) apogee at earth and perigee at Mars.
- (B) both apogee and perigee at earth.
- (C) apogee at Mars and perigee at earth.
- (D) both apogee and perigee at Mars.
- Q.9 The governing equation for the static transverse deflection of a beam under an uniformly distributed load, according to Euler-Bernoulli (engineering) beam theory, is a
 - (A) 2nd order linear homogenous partial differential equation.
 - (B) 4th order linear non-homogenous ordinary differential equation.
 - (C) 2nd order linear non-homogenous ordinary differential equation.
 - (D) 4th order nonlinear homogenous ordinary differential equation.
- 0.10The Poisson's ratio, ν of most aircraft grade metallic alloys has values in the range:
 - $(A) -1 \le \nu \le 0$
- (B) $0 \le \nu \le 0.2$
- (C) $0.2 \le \nu \le 0.4$
- (D) $0.4 \le \nu \le 0.5$

- (A) 0
- (B) 2
- (C) 4

(D) 8

Q.12 If u(t) is a unit step function, the solution of the differential equation $m\frac{d^2x}{dt^2} + kx = u(t)$ in Laplace domain is

- (A) $\frac{1}{s(ms^2 + k)}$ (B) $\frac{1}{ms^2 + k}$ (C) $\frac{s}{ms^2 + k}$ (D) $\frac{1}{s^2(ms^2 + k)}$

Q.13 The general solution of the differential equation $\frac{dy}{dx} - 2\sqrt{y} = 0$ is

- (A) $y \sqrt{x} + C = 0$ (B) y x + C = 0 (C) $\sqrt{y} \sqrt{x} + C = 0$ (D) $\sqrt{y} x + C = 0$

During the ground roll manoeuvre of an aircraft, the force(s) acting on it parallel to the direction of Q.14 motion

(A) is thrust alone.

- (B) is drag alone.
- (C) are both thrust and drag.
- (D) are thrust, drag and a part of both weight and lift.

An aircraft in a steady climb suddenly experiences a 10% drop in thrust. After a new equilibrium is Q.15 reached at the same speed, the new rate of climb is

(A) lower by exactly 10%.

(B) lower by more than 10%.

(C) lower by less than 10%.

(D) an unpredictable quantity.

Q.16 In an aircraft, the dive manoeuvre can be initiated by

- (A) reducing the engine thrust alone.
- (B) reducing the angle of attack alone.
- (C) generating a nose down pitch rate.
- (D) increasing the engine thrust alone.

In an aircraft, elevator control effectiveness determines O.17

- (A) turn radius.
- (B) rate of climb.
- (C) forward-most location of the centre of gravity.
- (D) aft-most location of the centre of gravity.

The Mach angle for a flow at Mach 2.0 is Q.18

- (A) 30°
- (B) 45°
- $(C) 60^{\circ}$
- (D) 90°

Q.19 For a wing of aspect ratio AR, having an elliptical lift distribution, the induced drag coefficient is (where C_L is the lift coefficient)

- (B) $\frac{C_L^2}{\pi AR}$
- (C) $\frac{C_L}{2\pi AR}$ (D) $\frac{C_L^2}{\pi AR^2}$

Bernoulli's equation is valid under steady state Q.20

(A) only along a streamline in inviscid flow, and between any two points in potential flow.

- (B) between any two points in both inviscid flow and potential flow.
- (C) between any two points in inviscid flow, and only along a streamline in potential flow.
- (D) only along a streamline in both inviscid flow and potential flow.

Q.21	The ratio of flig	ht speed to the exhaust ve	elocity for maximum pr	opulsion efficiency is	0
	(A) 0.0	(B) 0.5	(C) 1.0	(D) 2.0	13
Q.22	The ideal static	pressure coefficient of a	diffuser with an area rat	io of 2.0 is	
	(A) 0.25	(B) 0.50	(C) 0.75	(D) 1.0	
Q.23				on Mars for earth return. T malized by the acceleration of	
	(A) the bottom (C) earth's stand	of the crater on Mars. lard sea level.	(B) Mars standa (D) the same de	rd "sea level". pth of the crater on earth.	2.
Q.24	In a semi-monoc carriers of	coque construction of an	aircraft wing, the skin a	nd spar webs are the primar	у
	(B) normal (ben (C) shear stresse	es due to an aerodynamic ding) stresses due to aero es due to aerodynamic for es due to aerodynamic for	dynamic forces. ces alone.	Cil	
Q.25	-	decrement measured for e of the damping factor in		gle degree of freedom syste	m is
	(A) 0.5	(B) 1.0	(C) 1.5	(D) 2.0	
_	a positive whole	e number, or a positiv	e real number with	ver to each of these que maximum of 2 decimal p	
Q.26	The integration	$\int_{0}^{\infty} x^{3} dx$ computed using t	rapezoidal rule with <i>n</i> :	= 4 intervals is	
Q.27				150 m/s at 2500 m altitude. to 3000 m altitude is	The
Q.28	pressure and ten		d 290 K respectively (sp	n flow of 60 m/s. If the ambi pecific gas constant is 287 J/	
Q.29	weight of 25 g/r		neats 1.2. The universal	and the products have mole gas constant is 8314 J/kg-n	
Q.30	The mode sha	pes of an un-damped	two degrees of free	dom system are $\{1 \ 0.5\}$	$\right\}^T$ and
	$\{1 - 0.675\}^T$. amplitude (in n	The corresponding natural	ral frequencies are 0.45 first degree of freedom	Hz and 1.2471 Hz. The man due to an initial displace	aximum

Questions Q.31 to Q.55 are multiple choice type.

- The n^{th} derivative of the function $y = \frac{1}{x+3}$ is
- (A) $\frac{(-1)^n n!}{(x+3)^{n+1}}$ (B) $\frac{(-1)^{n+1} n!}{(x+3)^{n+1}}$ (C) $\frac{(-1)^n (n+1)!}{(x+3)^n}$ (D) $\frac{(-1)^n n!}{(x+3)^n}$
- Student Bounty.com
- The volume of a solid generated by rotating the region between semi-circle $y = 1 \sqrt{1}$ O.32 straight line y = 1, about x axis, is

 - (A) $\pi^2 \frac{4}{3}\pi$ (B) $4\pi^2 \frac{1}{3}\pi$ (C) $\pi^2 \frac{3}{4}\pi$

- One eigenvalue of the matrix $A = \begin{bmatrix} 2 & 7 & 10 \\ 5 & 2 & 25 \\ 1 & 6 & 5 \end{bmatrix}$ is -9.33. One of the other eigenvalues is 0.33
 - (A) 18.33
- (B) -18.33
- (D) 18.33+9.33i
- If an aircraft takes off with 10% less fuel in comparison to its standard configuration, its range is Q.34
 - (A) lower by exactly 10%.

(B) lower by more than 10%.

(C) lower by less than 10%.

- (D) an unpredictable quantity.
- An aircraft has an approach speed of 144 kmph with a descent angle of 6.6°. If the aircraft load Q.35 factor is 1.2 and constant deceleration at touch down is 0.25g (g = 9.81 m/s²), its total landing distance approximately over a 15 m high obstacle is
 - (A) 1830 m.
- (B) 1380 m.
- (C) 830 m.
- (D) 380 m.
- An aircraft is trimmed straight and level at true air speed (TAS) of 100 m/s at standard sea level Q.36 (SSL). Further, pull of 5 N holds the speed at 90 m/s without re-trimming at SSL (air density = 1.22 kg/m³). To fly at 3000 m altitude (air density = 0.91 kg/m³) and 120 m/s TAS without re-trimming, the aircraft needs
 - (A) 1.95 N upward force.

(B) 1.95 N downward force.

(C) 1.85 N upward force.

- (D) 1.75 N downward force.
- An oblique shock wave with a wave angle β is generated from a wedge angle of θ . The ratio of the Mach number downstream of the shock to its normal component is
 - (A) $\sin(\beta \theta)$
- (B) $\cos(\beta \theta)$
- (C) $\sin(\theta \beta)$
- (D) $\cos(\theta \beta)$
- O.38 In a closed-circuit supersonic wind tunnel, the convergent-divergent (C-D) nozzle and test section are followed by a C-D diffuser to swallow the starting shock. Here, we should have the
 - (A) diffuser throat larger than the nozzle throat and the shock located just at the diffuser throat.
 - (B) diffuser throat larger than the nozzle throat and the shock located downstream of the diffuser throat.
 - (C) diffuser throat of the same size as the nozzle throat and the shock located just at the diffuser
 - (D) diffuser throat of the same size as the nozzle throat and the shock located downstream of the diffuser throat.

Q.39 A vortex flowmeter works on the principle that the Strouhal number of 0.2 is a constant range of flow rates. If the bluff-body diameter in the flowmeter is 20 mm and the pie transducer registers the vortex shedding frequency to be 10 Hz, then the velocity of the flow be measured as (A) 0.1 m/s(B) 1 m/s(C) 10 m/s(D) 100 m/s 0.40 The stagnation temperatures at the inlet and exit of a combustion chamber are 600 K and 1200 K, respectively. If the heating value of the fuel is 44 MJ/kg and specific heat at constant pressure for

- air and hot gases are 1.005 kJ/kg.K and 1.147 kJ/kg.K respectively, the fuel-to-air ratio is
 - (A) 0.0018
 - (B) 0.018(C) 0.18
- (D) 1.18
- A solid propellant of density 1800 kg/m³ has a burning rate law $r = 6.65 \times 10^{-3} p^{0.45}$ mm/s, where p0.41 is pressure in Pascals. It is used in a rocket motor with a tubular grain with an initial burning area of 0.314 m². The characteristic velocity is 1450 m/s. What should be the nozzle throat diameter to achieve an equilibrium chamber pressure of 50 bar at the end of the ignition transient?
 - (A) 35 mm
- (B) 38 mm
- (C) 41 mm
- (D) 45 mm
- A bipropellant liquid rocket motor operates at a chamber pressure of 40 bar with a nozzle throat Q.42 diameter of 50 mm. The characteristic velocity is 1540 m/s. If the fuel-oxidizer ratio of the propellant is 1.8, and the fuel density is 900 kg/m³, what should be the minimum fuel tank volume for a burn time of 8 minutes
 - (A) 1.65 m^3
- (B) 1.75 m^3
- (C) 1.85 m^3
- (D) 1.95 m^3
- The propellant in a single stage sounding rocket occupies 60% of its initial mass. If all of it is 0.43 expended instantaneously at an equivalent exhaust velocity of 3000 m/s, what would be the altitude attained by the payload when launched vertically?
 - [Neglect drag and assume acceleration due to gravity to be constant at 9.81 m/s².]

- (A) 315 km (B) 335 km (C) 365 km (D) 385 km The Airy stress function, $\phi = \alpha x^2 + \beta xy + \gamma y^2$ for a thin square panel of size $l \times l$ automatically 0.44 satisfies compatibility. If the panel is subjected to uniform tensile stress, σ_{o} on all four edges, the traction boundary conditions are satisfied by
 - (A) $\alpha = \sigma_o / 2; \beta = 0; \gamma = \sigma_o / 2.$ (C) $\alpha = 0; \beta = \sigma_o / 4; \gamma = 0.$
- (B) $\alpha = \sigma_{\alpha}; \beta = 0; \gamma = \sigma_{\alpha}$.
- (D) $\alpha = 0; \beta = \sigma_0 / 2; \gamma = 0.$
- The boundary condition of a rod under longitudinal vibration is changed from fixed-fixed to fixedfree. The fundamental natural frequency of the rod is now k times the original frequency, where k is
- (B) 2
- (C) $\frac{1}{\sqrt{2}}$ (D) $\sqrt{2}$
- spring-mass system is viscously damped with a viscous damping constant c. The energy Q.46 dissipated per cycle when the system is undergoing a harmonic vibration $XCos\omega_d t$ is given by
 - (A) $\pi c \omega_{J} X^{2}$

- (B) $\pi \omega_d X^2$ (C) $\pi c \omega_d X$ (D) $\pi c \omega_d^2 X$
- Buckling of the fuselage skin can be delayed by Q.47
 - (A) increasing internal pressure.
 - (B) placing stiffeners farther apart.
 - (C) reducing skin thickness.
 - (D) placing stiffeners farther and decreasing internal pressure.

Common Data Questions

Common Data for Questions 48 and 49:

Student Bounty.com A wing and tail are geometrically similar, while tail area is one-third of the wing area and distance bet two aerodynamic centres is equal to wing semi-span (b/2). In addition, following data is applicable $\epsilon_{\alpha} = 0.3, C_L = 1.0, C_{L_{\alpha}} = 0.08/\deg_{\alpha}, \overline{c} = 2.5m, b = 30m, C_{M_{\alpha}} = 0, \eta_t = 1.$ The symbols have their usual aerodynamic interpretation.

- The maximum distance that the centre of gravity can be behind aerodynamic centre without Q.48 destabilizing the wing-tail combination is
 - (A) 0.4 m
- (B) 1.4 m
- (C) 2.4 m
- (D) 3.4 m
- The angle of incidence of tail to trim the wing-tail combination for a 5% static margin i 0.49
 - $(A) -1.4^{\circ}$
- $(B) -0.4^{\circ}$
- $(C) 0.4^{\circ}$

Common Data for Questions 50 and 51:

A thin long circular pipe of 10 mm diameter has porous walls and spins at 60 rpm about its own axis. Fluid is pumped out of the pipe such that it emerges radially relative to the pipe surface at a velocity of 1 m/s. [Neglect the effect of gravity.]

- What is the radial component of the fluid's velocity at a radial location 0.5 m from the pipe axis?
 - (A) 0.01 m/s
- (B) 0.1 m/s
- (C) 1 m/s
- (D) 10 m/s
- What is the tangential component of the fluid's velocity at the same radial location as above? 0.51
 - (A) 0.01 m/s
- (B) 0.03 m/s
- (C) 0.10 m/s
- (D) 0.31 m/s

Linked Answer Questions

Statement for Linked Answer Questions 52 and 53:

Air at a stagnation temperature of 15°C and stagnation pressure 100 kPa enters an axial compressor with an absolute velocity of 120 m/s. Inlet guide vanes direct this absolute velocity to the rotor inlet at an angle of 18° to the axial direction. The rotor turning angle is 27° and the mean blade speed is 200 m/s. The axial velocity is assumed constant through the stage.

- The blade angle at the inlet of the rotor is
- (B) 38.5°
- $(C) 48.5^{\circ}$
- (D) 59.5°
- Q.53 If the mass flow rate is 1 kg/s, the power required to drive the compressor is
 - (A) 50.5 kW
- (B) 40.5 kW
- (C) 30.5 kW
- (D) 20.5 kW

Statement for Linked Answer Questions 54 and 55:

A thin-walled spherical vessel (1 m inner diameter and 10 mm wall thickness) is made of a material with $|\sigma_v| = 500 \,\mathrm{MPa}$ in both tension and compression.

- The internal pressure p_y at yield, based on the von Mises yield criterion, if the vessel is floating in space, is approximately
 - (A) 500 MPa
- (B) 250 MPa
- (C) 100 MPa
- (D) 20 MPa
- If the vessel is evacuated (internal pressure = 0) and subjected to external pressure, yielding Q.55 according to the von Mises yield criterion (assuming elastic stability until yield)
 - (A) occurs at about half the pressure p_v .
- (B) occurs at about double the pressure p_y .
- (C) occurs at about the same pressure p_y .
- (D) never occurs.

General Aptitude (GA) Questions

Q. 56 – Q. 60 carry one mark each.

				5
2012				GENERAL APTITU Online
Gener	al Aptitude (GA)	Questions		THE.
Q. 56	- Q. 60 carry one	mark each.		GITE
Q.56	Choose the most app sentence:	ropriate alternative from	the options given belo	GENERAL APTITU Inline ow to complete the following
	I to have bough	t a diamond ring.		
	(A) have a liking(C) would like		(B) should have lik (D) may like	ed
Q.57	Choose the most app sentence:	ropriate alternative from	the options given belo	ow to complete the following
	Food prices aga	in this month.		CA SE
	(A) have raised(C) have been rising		(B) have been raisin (D) have arose	ng
Q.58	Choose the most app sentence:	ropriate alternative from	the options given belo	ow to complete the following
		went on to implement already and one mo		able measure, arguing that ke a difference.
	(A) reflective	(B) utopian	(C) luxuriant	(D) unpopular
Q.59	Choose the most app sentence:	ropriate alternative from	the options given belo	ow to complete the following
	To those of us who	had always thought hin	n timid, his came	as a surprise.
	(A) intrepidity	(B) inevitability	(C) inability	(D) inertness
Q.60	The arithmetic mean numbers is	of five different natural	numbers is 12. The lar	rgest possible value among the
46	(A) 12	(B) 40	(C) 50	(D) 60
Q. 61	- Q. 65 carry two :	marks each.		
Q.61	that A hits the convic		ability that B hits the c	aping convict. The probability convict. If the probability of the vict is
	(A) 0.14	(B) 0.22	(C) 0.33	(D) 0.40

Student Bounty.com GENERAL APTITU 2012

Q.62 The total runs scored by four cricketers P, Q, R, and S in years 2009 and 2010 are give following table:

Player	2009	2010
P	802	1008
Q	765	912
R	429	619
S	501	701

The player with the lowest percentage increase in total runs is

- (A) P
- (B) Q
- (C) R
- (D) S
- Q.63 If a prime number on division by 4 gives a remainder of 1, then that number can be expres
 - (A) sum of squares of two natural numbers
 - (B) sum of cubes of two natural numbers
 - (C) sum of square roots of two natural numbers
 - (D) sum of cube roots of two natural numbers
- Q.64 Two points (4, p) and (0, q) lie on a straight line having a slope of 3/4. The value of (p)
 - (A) -3
- (B) 0
- (D) 4
- Q.65 In the early nineteenth century, theories of social evolution were inspired less by Biology than by the conviction of social scientists that there was a growing improvement in social institutions. Progress was taken for granted and social scientists attempted to discover its laws and phases.

Which one of the following inferences may be drawn with the greatest accuracy from the above passage?

Social scientists

- (A) did not question that progress was a fact
- (B) did not approve of Biology.
- (C) framed the laws of progress.
- (D) emphasized Biology over Social Sciences.

END OF THE QUESTION PAPER

GATE 2012 - Answer Key - Paper : AE

Paper	Question no.	Key
AE	1	С
AE	2	С
AE	3	В
AE	4	D
AE	5	В
AE	6	С
AE	7	С
AE	8	С
AE	9	В
AE	10	С
AE	11	С
AE	12	А
AE	13	D
AE	14	D
AE	15	В
AE	16	С
AE	17	С
AE	18	А
AE	19	В
AE	20	Α
AE	21	С
AE	22	Marks to All
AE	23	C \
AE	24	D
AE	25	D
AE	26	0.26 to 0.27
AE	27	13 to 14
AE	28	1.1 to 1.2
AE	29	1430 to 1440
AE	30	2
AE	31	A
AE	32	A
AE	33	A
AE	34	В
AE	35	Marks to All

		State	
ey - Pape	er : AE	Key B A B B	
Paper	Question no.	Key	8
AE	36	В	·c
AE	37	A	,00
ΑE	38	В	2
ΑE	39	В	
ΑE	40	В	
AE	41	В	
ΑE	42	В	
ΑE	43	D	
ΑE	44	A	
ΑE	45	A	
AE	46	A	
AE	47	Α	
AE	48	В	
AE	49	Α	
AE	50	А	
AE	51	Marks to All	
AE	52	Marks to All	
AE	53	Marks to All	
AE 🕖	54	D	
AE	55	С	
AE	56	С	
AE	57	С	
AE	58	D	
AE	59	А	
AE	60	С	
AE	61	А	
AE	62	В	
ΑE	63	Α	
ΑE	64	С	
ΑE	65	A	