



COMPUTER SCIENCE

0478/21

Paper 2

October/November 2018

MARK SCHEME

Maximum Mark: 50

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge International will not enter into discussions about these mark schemes.

Cambridge International is publishing the mark schemes for the October/November 2018 series for most Cambridge IGCSE™, Cambridge International A and AS Level components and some Cambridge O Level components.

PUBLISHED**Generic Marking Principles**

These general marking principles must be applied by all examiners when marking candidate answers. They should be applied alongside the specific content of the mark scheme or generic level descriptors for a question. Each question paper and mark scheme will also comply with these marking principles.

GENERIC MARKING PRINCIPLE 1:

Marks must be awarded in line with:

- the specific content of the mark scheme or the generic level descriptors for the question
- the specific skills defined in the mark scheme or in the generic level descriptors for the question
- the standard of response required by a candidate as exemplified by the standardisation scripts.

GENERIC MARKING PRINCIPLE 2:

Marks awarded are always **whole marks** (not half marks, or other fractions).

GENERIC MARKING PRINCIPLE 3:

Marks must be awarded **positively**:

- marks are awarded for correct/valid answers, as defined in the mark scheme. However, credit is given for valid answers which go beyond the scope of the syllabus and mark scheme, referring to your Team Leader as appropriate
- marks are awarded when candidates clearly demonstrate what they know and can do
- marks are not deducted for errors
- marks are not deducted for omissions
- answers should only be judged on the quality of spelling, punctuation and grammar when these features are specifically assessed by the question as indicated by the mark scheme. The meaning, however, should be unambiguous.

GENERIC MARKING PRINCIPLE 4:

Rules must be applied consistently e.g. in situations where candidates have not followed instructions or in the application of generic level descriptors.

GENERIC MARKING PRINCIPLE 5:

Marks should be awarded using the full range of marks defined in the mark scheme for the question (however; the use of the full mark range may be limited according to the quality of the candidate responses seen).

GENERIC MARKING PRINCIPLE 6:

Marks awarded are based solely on the requirements as defined in the mark scheme. Marks should not be awarded with grade thresholds or grade descriptors in mind.

Question	Answer	Marks
Section A		
1(a)(i)	<p>1 mark for any meaningful array name related to Task 1 × 2 1 mark for correct data type AND use related to Task 1 × 2</p> <p>These are examples, many alternatives are valid.</p> <p>ItemCode ...string ...to store the item codes</p> <p>MenuItem ...string ...to store the menu items</p> <p>Price ...real ...to store the prices</p>	4

Question	Answer	Marks
1(a)(ii)	<p>1 mark for any meaningful variable name related to Task 2 × 2 1 mark for correct data type AND use related to Task 2 × 2, e.g.</p> <p>These are examples, many alternatives are valid.</p> <p>ItemCode ...string ...to allow items from menu to be input</p> <p>ItemCost ...real ...to hold price of current menu item</p> <p>TotalCost ...real ...to store current total price of the order</p> <p>Quantity ...integer ...to store the quantity of an item ordered</p>	4

Question	Answer	Marks
1(b)	<p>Any five from:</p> <ul style="list-style-type: none"> • Initialisation • Loop for entry order • Input of item code and quantity • Calculation of total price • Method of termination of loop e.g. use of flag • Generation of unique order code • Display Order... • ... display complete with unique order code, menu items, quantities, prices, total cost of order <p><i>Example algorithm</i></p> <pre> Total_Cost ← 0 Order_Complete ← FALSE Order_Item ← 0 Order_Number ← 0 Daily_Order_Counter ← 1 // The following would be repeated throughout the day REPEAT OUTPUT "Enter item code or X to finish" INPUT Item_Code[Order_Item] IF Item_Code[Order_Item] <> "X" THEN Menu_Count ← 0 Menu_Flag ← FALSE REPEAT IF Menu_Code[Menu_Count] = Item_Code[Order_Item] THEN Menu_Place[Order_Item] ← Menu_Count Menu_Flag ← TRUE Total_Cost ← Total_Cost + Menu_Price[Menu_Count] ELSE Menu_Count ← Menu_Count + 1 ENDIF UNTIL Menu_Flag ← TRUE OUTPUT "How many would you like? "</pre>	5

Question	Answer	Marks
1(b)	<pre> INPUT Item_Quantity[Order_Item] Order_Item ← Order_Item + 1 ELSE Order_Complete ← TRUE Order_Number ← Order_Number + 1 ENDIF UNTIL Order_Complete = TRUE OUTPUT "Order Number ", Order_Number Counter ← 0 WHILE Item_Code[Counter] <> "X" DO Menu_Count ← Menu_Place[Counter] OUTPUT Item_Code[Counter], " ", Menu_Item{Menu_Count}, " ", Price[Menu_Count], " ", Item_Quantity[Counter] Counter ← Counter + 1 ENDWHILE OUTPUT "Total cost of order = ", Total_Cost Daily_Order_Code[Daily_Order_Counter] ← Order_Number Daily_Total_Cost_of_Order[Daily_Order_Counter] ← Total_Cost </pre>	
1(c)	<p>Any four from:</p> <ul style="list-style-type: none"> • Explanation of using an input prompt and statement to enter the percent of the takings that are profit • Explanation of how the total takings are calculated • Explanation of how the percentage profits are calculated (from the input value) • Explanation of how the output is done // Explanation showing correct output statement with the daily takings, profit and percent value used in the calculation 	4

Question	Answer	Marks
1(d)	<p>1 mark for each correct test data item and related reason for Task 3 which requires a percentage to be input (Answers MUST relate to pre-release task) e.g.</p> <p>Test data: -10 Reason: To check that negative values of percentage are rejected (or can identify a loss)</p> <p>Test data: 7.5 Reason: To check that normal data is accepted</p> <p>Test data: 7Percent Reason: To check that incorrect data / data types are rejected</p>	3

Question	Answer	Marks														
Section B																
2	<p>1 mark for each correct line, maximum 5 marks</p> <table border="0" style="width: 100%;"> <thead> <tr> <th style="text-align: center; width: 50%;">Term</th> <th style="text-align: center; width: 50%;">Description</th> </tr> </thead> <tbody> <tr> <td style="border: 1px solid black; padding: 5px; text-align: center;">Top-down design</td> <td style="border: 1px solid black; padding: 5px; text-align: center;">Pre-written code to include in your own program to carry out a common task.</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px; text-align: center;">Structure diagram</td> <td style="border: 1px solid black; padding: 5px; text-align: center;">Shows the steps representing an algorithm using various shapes of boxes.</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px; text-align: center;">Flowchart</td> <td style="border: 1px solid black; padding: 5px; text-align: center;">Shows the hierarchy of the different components which make up a system.</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px; text-align: center;">Pseudocode</td> <td style="border: 1px solid black; padding: 5px; text-align: center;">Shows the values of variables as you manually test your program.</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px; text-align: center;">Library routine</td> <td style="border: 1px solid black; padding: 5px; text-align: center;">Breaks down a system into successively smaller pieces.</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px; text-align: center;">Trace table</td> <td style="border: 1px solid black; padding: 5px; text-align: center;">Describes a program using a simplified high-level notation.</td> </tr> </tbody> </table>	Term	Description	Top-down design	Pre-written code to include in your own program to carry out a common task.	Structure diagram	Shows the steps representing an algorithm using various shapes of boxes.	Flowchart	Shows the hierarchy of the different components which make up a system.	Pseudocode	Shows the values of variables as you manually test your program.	Library routine	Breaks down a system into successively smaller pieces.	Trace table	Describes a program using a simplified high-level notation.	5
Term	Description															
Top-down design	Pre-written code to include in your own program to carry out a common task.															
Structure diagram	Shows the steps representing an algorithm using various shapes of boxes.															
Flowchart	Shows the hierarchy of the different components which make up a system.															
Pseudocode	Shows the values of variables as you manually test your program.															
Library routine	Breaks down a system into successively smaller pieces.															
Trace table	Describes a program using a simplified high-level notation.															

Question	Answer	Marks
3	<p>1 mark for description 1 mark for example, e.g. To test if the value input falls between a given upper bound and a given lower bound ... If a month has to be input using an integer, it must be between 1 and 12 inclusive.</p> <p>1 mark for description 1 mark for example, e.g. To test if the data input is over/under a certain number of characters ... An international telephone number can be no longer than 15 digits.</p> <p>1 mark for description 1 mark for example, e.g. To test if the input is of the correct <u>data</u> type ... If the input is expecting integer(s) to be entered, it will not permit a string to be entered.</p>	6

Question	Answer	Marks
4(a)	<p>1 mark for each point:</p> <ul style="list-style-type: none"> • Expects 50 numbers to be input • Totals the numbers as they are entered / carries out a running total • Outputs the result after the numbers have all been entered 	3
4(b)	<p>1 mark for each point (max 3 marks):</p> <ul style="list-style-type: none"> • Correct initialisation of counter for REPEAT or WHILE loop ... • ... Correct loop statements and counter increment • ... Correct statements inside loop • ... Correct statements outside loop <p>e.g.</p> <pre>Total ← 0 Count ← 1 WHILE Count <= 50 DO INPUT Num Total ← Total + Num Count ← Count + 1 ENDWHILE OUTPUT Total</pre> <p style="text-align: right;">Accept alternative correct ranges e.g.</p> <pre>Count ← 0 WHILE Count < 50 DO</pre>	3

Question	Answer	Marks
4(b)	<pre>Total ← 0 Count ← 0 REPEAT INPUT Num Total ← Total + Num Count ← Count + 1 UNTIL Count = 50 OUTPUT Total</pre> <p>Accept alternative correct ranges e.g. Count ← 1 UNTIL Count > 50</p>	
4(c)	<p>1 mark for each correct point in description, e.g.</p> <ul style="list-style-type: none"> • Use a variable for the counter upper limit... • ... that is input by the user. <p>or</p> <ul style="list-style-type: none"> • loop using a condition control ... • ... until condition is met 	2

Question	Answer				Marks																																								
5(a)	<table border="1"> <thead> <tr> <th data-bbox="396 220 611 284">Flag</th> <th data-bbox="611 220 835 284">TestNum</th> <th data-bbox="835 220 1052 284">Num</th> <th data-bbox="1052 220 1274 284">OUTPUT</th> </tr> </thead> <tbody> <tr> <td data-bbox="396 284 611 347">True</td> <td data-bbox="611 284 835 347">7</td> <td data-bbox="835 284 1052 347">6</td> <td data-bbox="1052 284 1274 347"></td> </tr> <tr> <td data-bbox="396 347 611 411"></td> <td data-bbox="611 347 835 411"></td> <td data-bbox="835 347 1052 411">5</td> <td data-bbox="1052 347 1274 411"></td> </tr> <tr> <td data-bbox="396 411 611 475"></td> <td data-bbox="611 411 835 475"></td> <td data-bbox="835 411 1052 475">4</td> <td data-bbox="1052 411 1274 475"></td> </tr> <tr> <td data-bbox="396 475 611 539"></td> <td data-bbox="611 475 835 539"></td> <td data-bbox="835 475 1052 539">3</td> <td data-bbox="1052 475 1274 539"></td> </tr> <tr> <td data-bbox="396 539 611 603"></td> <td data-bbox="611 539 835 603"></td> <td data-bbox="835 539 1052 603">2</td> <td data-bbox="1052 539 1274 603"></td> </tr> <tr> <td data-bbox="396 603 611 667"></td> <td data-bbox="611 603 835 667"></td> <td data-bbox="835 603 1052 667">1</td> <td data-bbox="1052 603 1274 667">7</td> </tr> <tr> <td data-bbox="396 667 611 730"></td> <td data-bbox="611 667 835 730"></td> <td data-bbox="835 667 1052 730"></td> <td data-bbox="1052 667 1274 730"></td> </tr> <tr> <td data-bbox="396 730 611 794"></td> <td data-bbox="611 730 835 794"></td> <td data-bbox="835 730 1052 794"></td> <td data-bbox="1052 730 1274 794"></td> </tr> <tr> <td colspan="3" data-bbox="396 794 1052 874"> <----- 1 Mark -----> </td><td data-bbox="1052 794 1274 874"> <- 1 Mark - > </td></tr> </tbody> </table>				Flag	TestNum	Num	OUTPUT	True	7	6				5				4				3				2				1	7									<----- 1 Mark ----->			<- 1 Mark - >	2
Flag	TestNum	Num	OUTPUT																																										
True	7	6																																											
		5																																											
		4																																											
		3																																											
		2																																											
		1	7																																										
<----- 1 Mark ----->			<- 1 Mark - >																																										

Question	Answer	Marks																																								
5(b)	<table border="1" data-bbox="396 221 1276 874"> <thead> <tr> <th data-bbox="396 221 611 285">Flag</th> <th data-bbox="611 221 835 285">TestNum</th> <th data-bbox="835 221 1052 285">Num</th> <th data-bbox="1052 221 1276 285">OUTPUT</th> </tr> </thead> <tbody> <tr> <td data-bbox="396 285 611 351">True</td> <td data-bbox="611 285 835 351">6</td> <td data-bbox="835 285 1052 351">5</td> <td data-bbox="1052 285 1276 351"></td> </tr> <tr> <td data-bbox="396 351 611 416"></td> <td data-bbox="611 351 835 416"></td> <td data-bbox="835 351 1052 416">4</td> <td data-bbox="1052 351 1276 416"></td> </tr> <tr> <td data-bbox="396 416 611 481"></td> <td data-bbox="611 416 835 481"></td> <td data-bbox="835 416 1052 481">3</td> <td data-bbox="1052 416 1276 481"></td> </tr> <tr> <td data-bbox="396 481 611 547">False</td> <td data-bbox="611 481 835 547"></td> <td data-bbox="835 481 1052 547"></td> <td data-bbox="1052 481 1276 547"></td> </tr> <tr> <td data-bbox="396 547 611 612"></td> <td data-bbox="611 547 835 612"></td> <td data-bbox="835 547 1052 612"></td> <td data-bbox="1052 547 1276 612"></td> </tr> <tr> <td data-bbox="396 612 611 678"></td> <td data-bbox="611 612 835 678"></td> <td data-bbox="835 612 1052 678"></td> <td data-bbox="1052 612 1276 678"></td> </tr> <tr> <td data-bbox="396 678 611 743"></td> <td data-bbox="611 678 835 743"></td> <td data-bbox="835 678 1052 743"></td> <td data-bbox="1052 678 1276 743"></td> </tr> <tr> <td data-bbox="396 743 611 809"></td> <td data-bbox="611 743 835 809"></td> <td data-bbox="835 743 1052 809"></td> <td data-bbox="1052 743 1276 809"></td> </tr> <tr> <td data-bbox="396 809 611 874"></td> <td data-bbox="611 809 835 874"></td> <td data-bbox="835 809 1052 874"></td> <td data-bbox="1052 809 1276 874"></td> </tr> </tbody> </table> <p data-bbox="409 826 1258 858" style="text-align: center;"> <----- 1 Mark -----> <-----1 Mark -----> </p>	Flag	TestNum	Num	OUTPUT	True	6	5				4				3		False																								2
Flag	TestNum	Num	OUTPUT																																							
True	6	5																																								
		4																																								
		3																																								
False																																										
5(c)	1 mark for correct purpose e.g. Works out if the number entered is a prime number.	[1]																																								

Question	Answer	Marks																																										
6(a)	<table border="1" data-bbox="481 220 1348 547"> <thead> <tr> <th>Field</th> <th>Data type</th> </tr> </thead> <tbody> <tr> <td>PCID</td> <td>Text</td> </tr> <tr> <td>ScreenSize</td> <td>Number</td> </tr> <tr> <td>Type</td> <td>Text</td> </tr> <tr> <td>Price</td> <td>Currency</td> </tr> </tbody> </table> <p data-bbox="349 584 808 647">2 marks for 4 correct data types 1 mark for 2 or 3 correct data types</p>	Field	Data type	PCID	Text	ScreenSize	Number	Type	Text	Price	Currency	2																																
Field	Data type																																											
PCID	Text																																											
ScreenSize	Number																																											
Type	Text																																											
Price	Currency																																											
6(b)	<p data-bbox="349 683 1032 810">1 mark correct Fields included 1 mark correct Table and Show on all fields used 1 mark for correct sort, must be descending on Price 1 mark for correct criteria for the fields</p> <table border="1" data-bbox="481 850 1527 1241"> <tbody> <tr> <td>Field:</td> <td>PCID</td> <td>ScreenSize</td> <td>RAM</td> <td>Type</td> <td>HDD(Gb)</td> <td>Price</td> </tr> <tr> <td>Table:</td> <td>PCSTOCK</td> <td>PCSTOCK</td> <td>PCSTOCK</td> <td>PCSTOCK</td> <td>PCSTOCK</td> <td>PCSTOCK</td> </tr> <tr> <td>Sort:</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Descending</td> </tr> <tr> <td>Show:</td> <td><input checked="" type="checkbox"/></td> <td><input checked="" type="checkbox"/></td> <td><input checked="" type="checkbox"/></td> <td><input checked="" type="checkbox"/></td> <td><input checked="" type="checkbox"/></td> <td><input checked="" type="checkbox"/></td> </tr> <tr> <td>Criteria:</td> <td></td> <td></td> <td></td> <td>= "DT"</td> <td>>1000</td> <td></td> </tr> <tr> <td>or:</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Field:	PCID	ScreenSize	RAM	Type	HDD(Gb)	Price	Table:	PCSTOCK	PCSTOCK	PCSTOCK	PCSTOCK	PCSTOCK	PCSTOCK	Sort:						Descending	Show:	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Criteria:				= "DT"	>1000		or:							4
Field:	PCID	ScreenSize	RAM	Type	HDD(Gb)	Price																																						
Table:	PCSTOCK	PCSTOCK	PCSTOCK	PCSTOCK	PCSTOCK	PCSTOCK																																						
Sort:						Descending																																						
Show:	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>																																						
Criteria:				= "DT"	>1000																																							
or:																																												