MARK SCHEME for the October/November 2009 question paper

for the guidance of teachers

0445 DESIGN AND TECHNOLOGY

0445/03

Paper 3 (Resistant Materials), maximum raw mark 50

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

• CIE will not enter into discussions or correspondence in connection with these mark schemes.

CIE is publishing the mark schemes for the October/November 2009 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



	Page 2	Mark Scheme: Teachers' version	Syllabus	Paper
		IGCSE – October/November 2009	0445	03
		Section A		
1	(a) 1 mark If G cra	for each cramp shown positioned across ends of frame mp is shown, award 0 marks.		[2]
	(b) Sash cr	amps.		[1]
2	A HammeB Scrap wC Folding	er. Ignore any reference to 'pin', 'ball pein' etc. and awar vood, waste wood, block of wood, but not 'former'. bars, bending irons.	rd 1 mark.	[1] [1] [1]
3	Grain must l If 3 layers a	be shown at right angles to next layer. 1 mark if only 2 l re drawn with grain shown in same direction award 0 m	ayers shown. arks.	[2]
4	Draw filing. No alternat	ive answers.		[1]
5	Two method plane to position award b shooting	Is of planing end grain include: o middle, stop, plane to middle from opposite end; scrapwood at end of wood at plane across; penefit of doubt to wood positioned at side of that being g board.	planed.	[1 + 1]
6	(a) Odd leg Used to Candida	or 'Jenny' calipers. Accept 'calipers'. draw lines on metal or plastic parallel to an edge. ates can still achieve 1 mark for correct description even	n if incorrectly na	[1] [1] amed. [2]
	(b) Rule sh	own under foot of calipers with point on required dista	nce.	[1]
7	Completed j	oint 0–3 dependent upon accuracy/clarity.		[3]
8	Suitable spe solid wood t Do not acce	ecific finish for: able top: polyurethane varnish, varnish, wax polish or c ept French polish.	ellulose lacquer	[1]
	wooden cho Do not acce	pping board for vegetables: olive oil, linseed oil or no fine to fine the set 'glasspaper' or references to covering with a plastic	nish. Iaminate.	[1]
9	Soft drinks t Canoe: GRF Bucket: inje	pottle: extrusion blow moulding, blow moulding. Do not P, moulding, lay up. ction moulding.	accept 'blow for	ming'. [1] [1] [1]
10	 A Tool po B Bed C Lead so There are n 	st rew o alternative correct answers to these 3 terms.		[1] [1] [1]

© UCLES 2009

Page 3	Mark Scheme: Teachers' version	Syllabus	Paper		
	IGCSE – October/November 2009	0445	03		

Section B

- **11 (a)** Two reasons include: easy to bend, lightweight, does not corrode outside, easy to work. [1 + 1] Accept 'light' but not references to quality of sound produced by metal.
 - (b) (i) Two marking out tools include: rule, scriber, try square, odd legs. [1 + 1] Accept 'scribe', 'marker pen', 'felt tip'. Do not accept: 'square', 'pencil', 'divider' or 'template' as this is given in part (ii).
 - (ii) One benefit of using a template: allows you to mark out on paper or card accurately then glue onto metal, quick, saves time, accurate. [1]
 - (iii) Use of tin snips/named and sketched correctly. (0–2)
 Could also include use of guillotine.
 Do not accept: 'hacksaw' or use of 'vice' as the metal should be clamped flat.

Notes relating to holding sheet metal/accuracy of technical detail. (1) [3]

- (c) Jig can saw 3 different lengths.(1)Held securely.Use of vice 1 mark onlyLocation of saw blade.(1)Accuracy/quality of details.(0-2)[6]
- (d) (i) Tube located in vice jaws accurately. (1) 45° recesses to grip tube. (1)



If a circle is drawn without the 45° recesses to grip tube award 1 mark.

	(ii)	Purpose of centre punch before drilling: to provide a guide for the drill. To prevent slipping. Do not accept: 'shows where you will drill'.	(1) (1)	[2]
(e)	(i)	Suitable finish: lacquer, anodised, electroplating. Do not accept: 'galvanised'.		[1]
	(ii)	If finish is incorrect in part (i) part (ii) can still be correct. Aluminium prepared by means of wet and dry paper, emery cloth	(1)	

Aluminium prepared by means of wet and dry paper, emery cloth.(1)Various grades – finish with fine grade.(1)[2]

© UCLES 2009

www.xtremepapers.net

[2]

Page 4	Mark Scheme: Teachers' version	Syllabus	Paper		
	IGCSE – October/November 2009	0445	03		

(f) Modification needs to include a simple bracket or provision in back of support to be screwed to a wall.

Award up to 2 marks for practical idea.	(0–2)
Clearly communicated with accurate technical detail.	(0-2)
Technical detail could include:	
the materials the modification is made from, the sizes and	d/or the joints involved.

12 (a) Two items of research include: size of DVD, number of DVDs, location, space for rack, available materials, evaluation/consideration of existing racks, anthropometric data. [1 + 1]

If candidate gives 2 answers such as 'length of DVD' or 'width of DVD' award only 1 mark for reference to sizes.

Do not accept: 'weight of DVD', or vague references to 'materials' or 'safety'.

(b) (i) Accept any correct stage/process even if not in correct order.
 Do not accept: repeated processes or repeated tools/equipment.

Stages	Process	Tools/Equipment					
1	Marking out	Chinagraph pencil, felt marker, scriber, rule, try square					
2	Drill hole	Drilling machine, drill					
3	Insert saw blade, saw to shape	Coping saw, Hegner saw or equivalent. Not jig saw					
4	File to shape	Flat or hand file					

Accept any **one** correct process or tool.

- (ii) Problems include:
 - snagging/cracking when drilling sheet;
 - can be brittle;
 - sawing or filing too high in the vice;
 - scratching surface while working;
 - using Tensol cement;
 - personal injury.

Overcome:

- clamp work piece down;
- support with wooden blocks;
- lower position in vice/support;
- retain backing sheet;
- well ventilated room;
- goggles.

[7]

[4]

[1]

[1]

© UCLES 2009

	Ра	ge 5		Mark Scheme: Teachers' version						S	Syllab	us		Paper					
					IGC	SE –	Octo	ber/N	ove	mber	2009				0445	5		03	
	(c)	 (i) Two tools used to finish include: drawfiling/file, wet and dry paper, [silicone carbide paper], polishing mop, polishing compound, Perspex polish. Do not accept: 'water paper'. (ii) Edges are finished before bending because it is much easier to work flat. d) Strip heater/line bender/oven named and drawn showing plastic being heated. Means of holding plastic to required angle/use of former, including method of ref cooling. Accuracy of added technical notes/detail. 							le, we shing	et ar com	nd dry npour	y pap nd, P	er, erspe	x poli:	sh.		[1] [1]		
											[1]								
	(d)								rete	(0–2) ention w (0–2) (0–2)	/hile [6]								
	(e)	Pra Det	ctical ails o	l idea i of mate	ncludir rials, c	g use onstru	of action	ddition ns, fitti	al 'fl ngs.	aps' c	or brad	cket						(0–3) (0–2)	[5]
		Mus	st inv	olve a	modifi	cation	to th	e rack	in F	- ig. 10	and	not	a cor	nplet	elv ne	w de	sigr	n, other	wise
		award 0 marks. Candidates can achieve maximum 3 marks for a practical idea but 0 incorrect/inappropriate details.								0	marks	for							
13	(a)	(i)	Harc Apai	dwood rt from	: beech balsa	n. Acc wood	ept a acce	wide pt any	rang ⁄ nar	e of p ned h	ossib ardwo	le ha bod.	ardwo	oods	used	today	<i>י</i> .		[1]
		(ii)	Prop Can	perties didate	include s can a	e: extr ichiev	remel e 1 m	y harc nark fo	l, clo or thi	ose-gra s part	ained even	, de if th	nse, ' le an	will n swer	ot spl to pa	it easi rt (i) is	ily. s ind	correct.	[1]
	(b)	The viev	cons v of tl	structio he join	ons dra t, othe	wn m wise	ust re awar	elate to d max	o the imur	e parts n 2 m	/shap arks.	e of	f the t	truck	and r	not jus	st be	e a gene	əric
		Car inco	ndidat prrect	tes ca t.	n draw	a cori	rect jo	oint ar	nd ac	chieve	maxi	imur	m 3 n	narks	s ever	if the	e na	med joi	nt is
		Two	o con	structi	ons inc	lude:	dowe	elled jo	oint,	housir	ng, m	ortis	e and	d ten	on, bı	ıtt joir	nt*.		
		*Butt joints must be shown with nails or screws and glue for maximum 3 marks othe maximum 1 mark.								s other	vise								
		Acc Do	ept 2 not a	2 different accept	ent var K-D fil	ations tings.	s of a	housi	ng jo	oint or	a mc	ortise	e and	tenc	on joir	t.			
		1 m Cor	ark fo nplete	or corr ed join	ectly na t 0–3 c	amed Iepen	and dent	approj upon a	priat accu	e joint racy/c	:. clarity								[1] [3]
		1 m	ark fo	or corr	ectly n	amed	and	annroi	oriat	a inint									[1]

1 mark for correctly named and appropriate joint.[1]Completed joint 0–3 dependent upon accuracy/clarity.[3]

© UCLES 2009

Pa	ge 6	Mark Scheme: Teachers' version	Syllabus	Pa	aper
			03		
(c)	Suitable/ Three dil Accurac	practical method of fixing to sides of truck. ferent heights : method of adjustment. y of technical detail.		(0–2) (0–2) (0–2)	[6]
(d)	Use of n Safe in u	uts, bolts, screws, star washers, captive caps, circlips t ise.	o fix.	(0–2) (1)	[3]
(e)	Allow eit	her wood or metal turning lathe. ust be a description of the stages.			
	Preparat Setting u Method o	ion of wood for either between centres or faceplate. p on faceplate or between centres. of turning wood to shape/size.		(0–2) (0–2) (0–2)	[6]

© UCLES 2009