



**Especial Information for Invigilators: NIL**

**Information for Candidates:**

1. Erlang Loss formula recursive evaluation:

$$E_N(\rho) = \frac{\rho E_{N-1}(\rho)}{N + \rho E_{N-1}(\rho)}$$
$$E_0(\rho) = 1.$$

2. Engset Loss formula recursive evaluation (for a fixed  $M$  and  $p = \alpha/1 + \alpha$ ):

$$e_N = \frac{(M - N + 1)\alpha e_{N-1}}{N + (M - N + 1)\alpha e_{N-1}}$$
$$e_0 = 1.$$
$$\alpha = \lambda/\mu.$$

3. Traffic capacity on basis of Erlang B formula (next page).

1.

a) For the system in Figure 1.1 assume:

- The  $M$  sources act independently.
- The call arrival rate from a free source is Poisson with parameter  $\lambda$ .
- The link is composed of  $N$  channels.
- The channel holding time is a negative exponential with parameter  $1/\mu$ .
- There is full availability access.

i) Derive the Global balance equations.

[6]

ii) Derive the Local balance equations.

[6]

b) Consider the system of part a) and assume the following parameters:

- $N = 4$  (channels link).
- $M = 6$  (sources of traffic).
- The call rate of a free source = 0.5 [calls/minute].
- The mean holding time = 2 [minutes].

Determine the total traffic carried by the link.

[8]




Figure 1.1

2.

- a) A 15-channel communication link is offered pure chance traffic with an arrival rate of 3 [demands/minute] and a mean holding time of 3 [minutes].

If blocked calls are allowed to overflow onto a single-channel overflow link:

- i) Determine the mean of the traffic offered to the overflow link.
- i) Determine the mean traffic carried by the overflow link.

[10]

- b) In practice a local access switch may not give full-availability access to the link. That is, an arriving demand may be blocked even when the link is not saturated.

- i) Using a known definition of “loss factor”, describe and discuss a restricted availability model.
- ii) For the model described in b) i) derive the birth and death coefficients.

[10]

3.

a) For an M/M/K/N system

i) Show that the probability that the system is empty can be expressed by:

$$\pi_0 = \frac{1}{(A^K/K!)} \left[ \frac{(1-\rho)E_K(A)}{(1-\rho) + \rho(1-\rho^B)E_K(A)} \right]$$

ii) Define  $A, B, K, \rho$  and  $E_K(A)$ .

iii) Derive the probability that new arrivals are delayed.

iv) Derive the probability that new arrivals are blocked.

State clearly all the assumptions made.  
Explain all the steps of your derivations.

[10]

b) For the following priority schemes:

i) For the pre-emptive priority scheme: determine the expected value of residual time seen by class k traffic.

ii) For the non-pre-emptive priority scheme: determine the mean waiting time for class k traffic.

State clearly all the assumptions made.  
Explain all the steps of your derivation.

[10]

4.

- a) Consider a fluid flow model. The stationary probability  $F(x)$  that the buffer occupancy is less than or equal to  $x$ , given  $i$  sources in talkspurt, can be obtained from the following equation:

$$(i - C)\alpha \frac{\partial F_i(x)}{\partial x} = [N - (i - 1)]\lambda F_{i-1}(x) - [(N - i)\lambda + i\alpha]F_i(x) + (i + 1)\alpha F_{i+1}(x)$$

This can be written in matrix form as

$$\frac{dF(x)}{dx} D = F(x) M$$

The dimension of  $D$  and  $M$  is  $N \times N$ , where  $N$  is the number of traffic sources, and hence the general solution is given by:

$$F(x) = \sum_{i: \text{Re}[Z_i < 0]}^N a_i \phi_i e^{z_i x}$$

where  $z_i$  is the  $i$ -th eigenvalue and  $\phi_i$  is the corresponding  $i$ -th eigenvector of the eigenvector equation  $z_j \phi_j D = \phi_j M$ .

- i) Define the traffic source model and explain the meaning of the parameter  $\alpha$ .
- ii) Define and construct  $M$  and  $D$  for the system when  $N = 1$ .
- iii) Obtain the eigenvalues for the system when  $N = 1$ .
- iv) Discuss your results.

[10]

- b) In ATM admission control mechanisms, the measure of equivalent capacity is frequently used.

- i) Describe the motivations for using a stationary approximation of equivalent capacity
- ii) Derive the stationary approximation of equivalent capacity.
- iii) Describe the motivation for using a fluid-flow approximation of equivalent capacity.
- iv) Derive the fluid-flow approximation of equivalent capacity.

State clearly all the assumptions made.  
Explain all the steps of your derivations.

[10]

5.

a)

- i) Describe a way in which a composite Performance/Reliability assessment could be realised using the Performability model.
- ii) Describe and discuss assumptions made on a Markov Reward Model (MRM).
- iii) For the system in Figure 5.1.


assume:

- The Link 1 failure rate is  $\alpha$ .
- The Link 2 failure rate is  $\beta$ .
- The system can only be fully repaired at a rate  $\mu$  if both links are simultaneously in failure condition.

a) Define the state space of the system.

b) Derive the Markov chain representation of the fault tolerant system.

[10]

**Figure 5.1**

b) For a stochastic knapsack problem:

- i) Derive the blocking probability of an arriving class-k object.
- ii) Discuss the relationship between the knapsack problem and the Erlang loss system.

[10]



Department of Electrical and Electronic Engineering Examinations 2006  
 Model Answers and Mark Schemes  
 Paper Code: E9.05 - 507 -  
 CS 22

Confidential


First Examiner:  
 Second Examiner:

Traffic Theory and  
 Queueing Systems

Question Number etc. in left margin

Mark allocation in right margin

Q1  
 a)



2

i) global

$$[(M-i)\lambda + i\mu] \pi_i = (M-i+1)\lambda \pi_{i-1} + (i+1)\mu \pi_{i+1}$$

M = no sources

$\pi_i$  = equilibrium state probability in state i

$\lambda$  = calling rate / free source

$\mu$  = release rate / channel

4

ii) local

$$(M-i+1)\lambda \pi_{i-1} = i\mu \pi_i$$

+ discussion

(backwork extension)

4



Question Number etc. in left margin

Mark allocation in right margin

Q1  
5)

$$M=6, N=4$$

For  $N < M$ 

$$\rho_c = E(N_t) = Mp - [\pi_N(M, p) \times (M-N)p]$$

$$\pi_N(M, p) = e_N = \frac{(M-N+1)\alpha e_{N-1}}{N + (M-N+1)\alpha e_{N-1}}, e_0 = 1$$

(Recursion)

$$p = \frac{d}{d+\mu} = 0.5 \quad \alpha = \frac{\lambda}{\mu} = 1 = 0.5 \times 2$$

$$N=1 \quad e_1 = \frac{(6-1+1)}{1+(6-1+1)} = \frac{6}{7}$$

$$N=2 \quad e_2 = \frac{(6-2+1) \frac{6}{7}}{2 + (6-2+1) \frac{6}{7}} = \frac{30/7}{(14+30)/7} = \frac{30}{44}$$

$$N=3 \quad e_3 = 30/63$$

$$N=4 \quad e_4 = \frac{(6-4+1) \frac{30}{63}}{4 + (6-4+1) \frac{30}{63}} = \frac{90}{342}$$

$$\rho_c = 6 \cdot 0.5 - \frac{90}{342} \cdot (6-4) \cdot 0.5$$

$$= 2.7368$$

(Calculation of new  
example)

Question Number etc. in left margin

Mark allocation in right margin

Q2

a) offered traffic  $\rho_0 = \lambda \bar{h} = 9$  Erlangs

Using Koster modd

Mean of overflow traffic

$$m = E(N_t) = \rho E_n(\rho)$$

from table

$$m = 9 [0.02] = 0.18$$

Using Brockmeyer modd

Mean of the carried traffic

$$m = E(N_t) = \rho [E_n(\rho) - E_{n+1}(\rho)]$$

from table

$$m = 9 [0.02 - 0.011] = 0.081$$

(Calculation of new example) 5

b) Restricted availability

loss factor  $\beta_i = P[\text{arrival is blocked} | N_t = i]$

$i = 0, 1, \dots$

For restricted availability access

$0 < \beta_i < 1$  for at least one  $i < N$

The new birth coefficients  $\lambda_i' = (1 - \beta_i) \lambda_i$

Since  $P[\text{arrival in } (t, t + \Delta t) \text{ and not blocked} | N_t = i]$

$$= (\lambda_i \Delta t) (1 - \beta_i)$$

The death coefficient  $\mu_i = i \mu$

(book work) 10

Question Number etc. in left margin

Mark allocation in right margin

Q3 M/M/K/N

a)

local balance equation

$$\pi_i = \left( \frac{A^i}{i!} \right) \pi_0 \quad 0 \leq i \leq K$$

$$= \left( \frac{A^K}{K!} \right) \rho^{i-K} \pi_0 \quad K \leq i \leq K+B$$

$$\sum \pi_i = 1 = \left( \sum_{i=1}^K \left( \frac{A^i}{i!} \right) + \sum_{j=1}^B \left( \frac{A^K}{K!} \right) \rho^j \right) \pi_0$$

$$\Rightarrow S = \left( \frac{A^K}{K!} \right) \left[ E_K(A) + \frac{\rho(1-\rho^B)}{1-\rho} \right] \quad \left( \pi_0 = \frac{1}{S} \right)$$

Note

$$\sum_{j=1}^B \rho^j = \rho \sum_{j=0}^{B-1} \rho^j = \rho \left( \sum_{j=0}^{\infty} \rho^j - \sum_{k=B}^{\infty} \rho^k \right)$$

$$= \rho \left( \frac{1}{1-\rho} - \frac{\rho^B}{1-\rho} \right)$$

$$= \rho \left( \frac{1-\rho^B}{1-\rho} \right)$$

N = K + B (size system)

K = no servers

B = size Buffer

$$\rho = A/K$$

$$A = \lambda/\mu$$

$$E_K(A) = \frac{A^K/K!}{\sum_{j=0}^{\infty} (A^j/j!)}$$

(back work  
extension)

Question Number etc. in left margin

Mark allocation in right margin

Q3

a)  
(cont)

$$\begin{aligned} \text{iii)} P[\text{Delay}] &= P[\text{all } k \text{ servers busy / buffer not full}] \\ &= P[K \leq N_t < K+B] \\ &= \pi_K \left[ \frac{1 - \rho^B}{1 - \rho} \right] \end{aligned}$$

$$\begin{aligned} P[\text{loss}] &= P[\text{Buffer full}] \\ &= P[N_t = K+B] \\ &= \pi_{K+B} \rho^B \end{aligned}$$

b)

$$\text{i)} E(R) = \frac{1}{2} \sum_{i=1}^K \rho_i E(s_i^2) \sim E(R_k)$$

class  $k$  users can interrupt any lower-class service in progress. So the only contributors to  $E(R)$  will be from class  $k$  and above

ii)

$$E(W_k) = \frac{E(R)}{(1 - \sigma_{k-1})(1 - \sigma_k)}$$

$$\sigma_{k-1} = \sum_{i=1}^{k-1} \rho_i$$

derived starting from

$$\begin{aligned} E(W_1) &= E(R) + E(Q_1) E(s_1) \\ &= E(R) + \lambda_1 E(W_1) E(s_1) \end{aligned}$$

$$E(W_1) = \frac{E(R)}{1 - \rho_1}$$

(backwash  
+ discussion)

2

2

3


5



Question Number etc. in left margin

Mark allocation in right margin

Q4  
a)



$\frac{1}{\alpha}$  = average length of talk span

$$\frac{dF(x)}{dx} = F(x)M \rightarrow \frac{dF(x)}{dx} = F(x)M'$$

$$M' = MD'$$

$\mu = 1$  (one voice source)

$$M = \begin{bmatrix} -\alpha & \alpha \\ \alpha & -\alpha \end{bmatrix} = \begin{bmatrix} -\gamma & \gamma \\ 1 & -1 \end{bmatrix} \quad \gamma \equiv \frac{1}{\alpha}$$

$$D = \begin{bmatrix} -c\alpha & 0 \\ 0 & (1-c)\alpha \end{bmatrix} \quad D' = \begin{bmatrix} \frac{1}{c} & 0 \\ -c & \frac{1}{(1-c)} \end{bmatrix}$$

$$M' = \begin{bmatrix} \gamma/c & \gamma/(1-c) \\ -\gamma/c & -\gamma/(1-c) \end{bmatrix} \quad \alpha = 1 \text{ (normalised version)}$$

Eigenvalues given by:

$$zI - M' = 0$$

$$z = 0$$

$$z = \frac{\gamma}{c} - \frac{1}{1-c}$$

Stable system  $\Rightarrow \rho \equiv \left( \frac{\gamma}{1-\gamma} \right) \frac{1}{c} < 1$

$$z = - \frac{(1-\rho)(1+\gamma)}{1-c}$$

$$(z < 0)$$

(calculate of new state)

1

3

3

3

Question Number etc. in left margin

Mark allocation in right margin

Q4  
b)

Equivalent capacity

$$C_L = (m + k\sigma) R_p$$

$$m R_p = \text{mean}$$

$$\sigma R_p = \text{standard deviation}$$

$$k = k(QoS)$$

$$m = Np$$

$$\sigma^2 = Np(1-p) = m(1-p)$$

$$C = \frac{C_L}{R_p} \rightarrow C = m + k\sigma = Np + k\sqrt{Np(1-p)}$$

$$k(QoS) \sim P_L$$

$$i) P_L = \sum_{i=0}^N \frac{(i-c)\pi_i}{m}$$

$$ii) E = \sum_{i=0}^N \pi_i$$

i) large number of sources multiplexed

$$N \gg 1, p \ll 1$$

$$\pi_i = \binom{N}{i} p^i (1-p)^{N-i}$$

Approximated by the normal distribution

$$m = Np, \sigma^2 = Np(1-p)$$

$$P_L = \frac{1}{m} \int_0^{\infty} \frac{e^{-(x-m)^2/2\sigma^2}}{\sqrt{2\pi\sigma^2}} (x-c) dx$$

$$E = \int_0^{\infty} \frac{e^{-(x-m)^2/2\sigma^2}}{\sqrt{2\pi\sigma^2}} dx$$

$$\text{if } (c-m) > 3\sqrt{2}\sigma$$

$$E = \frac{\sigma e^{-(c-m)^2/2\sigma^2}}{\sqrt{2\pi} (c-m)}; P_L = \frac{1-p}{c-m} E$$

$$\ln(\sqrt{2\pi} E) = \ln(\sigma/(c-m)) - (c-m)^2/2\sigma^2$$

$$C_{LS} = m R_p + \underbrace{\sigma \sqrt{-\ln(2\pi) - 2\ln E}}_k R_p$$

(Derivation + bookwork explanation)

2

4

Question Number etc. in left margin

Mark allocation in right margin

Q4 ii) Effect of the access buffer

$$G(x) \sim A_p \rho^N e^{-\rho R x / R_p}$$

(probability buffer occupancy  $> x$ )

$$R = (1-\rho) \left(1 + \frac{\sigma}{\rho}\right) / \left(1 - \frac{C_L}{MR_p}\right)$$

$$\rho = \frac{M_p R_p}{C_L}$$

$$\text{if } \rho \sim 1 \quad A_p \rho^N \sim 1$$

$$P_L = e^{-\rho R x / R_p}$$

$$-\ln P_L = \rho R x / R_p$$

$$\frac{C_L}{R_p N} = \frac{1-k}{2} + \sqrt{\left(\frac{1-k}{2}\right)^2 + k_p}$$

$$C_{LF} = R_p N \left(\frac{1-k}{2}\right) + R_p N \sqrt{\left(\frac{1-k}{2}\right)^2 + k_p}$$

(heuristic  
+ explanation)

4



Question Number etc. in left margin

Mark allocation in right margin

5a i) Performability is a measure that quantifies a system's ability to perform in the presence of faults.

A Performability model is obtained by:

- Modelling the process  $X$  that represents the behaviour of the system and
- Defining the performance variable  $Y$  for each state of the system

ii) MRM

- If  $X(t)$  can be represented by a continuous-time finite-state Markov chain (CTMC), and
- Extend this process  $X(t)$  assigning rewards rates to its states



$$Q = \sum_{i=0}^N r_i z_i$$

$$P_i(t, y) = P[Y(t) \leq y | X(0) = s_0]$$

iii)

a) 00, 01, 10, 11 (link 1 failure, link 2 failure)

b)

		00	01	10	11
Q =	00	$-(\alpha + \mu)$	$\mu$	$\alpha$	0
	01	0	$-\alpha$	0	$\alpha$
	10	0	0	$-\mu$	$\mu$
	11	$\mu$	0	0	$-\mu$

(calculator of new sample)

Question Number etc. in left margin

Mark allocation in right margin

Q5  
b)

- i) - C resource units
  - Poisson arrival  $\lambda_k$
  - Exponential holding time  $1/\mu_k$
  - hold  $b_k$  resource units
  - pure loss system:  $m = (m_1, \dots, m_k)$ ;  $b = (b_1, \dots, b_k)$
- Admit class-k arrival if  $b_k < C - b \cdot m$

Dynamic Knapsack Problem

$$S \equiv \{m \in \mathbb{I}^k : b \cdot m \leq C\}$$

$x(t) = (x_1(t), \dots, x_k(t))$  state at t

$\{x(t)\}$  = aperiodic and irreducible Markov process over S

Blocking probability of class-k

$$B_k = \{m \in S : b \cdot m \leq C - b_k\}$$

Since arrivals are Poisson

$$B_k = 1 - \sum_{m \in S_k} \pi(m)$$

ii) The stochastic knapsack generalises the Erlang loss system. If there is only one class and all objects have size of unit, then the stochastic knapsack reduces to the Erlang loss system. The stochastic knapsack result is a multi-dimensional generalisation of the Erlang

(backwards)

5

5